

# OMEGA COMPRESSOR INVENTORY LIST



## CONTRACTOR - OIL LESS DIRECT DRIVE SERIES

MODEL NO.	VOLTAGE	HP	DESCRIPTION
MB-2000G	115V/1PH	2	Oil-less direct drive air compressor. Maintenance-free operation. Die-cast aluminum pump with cast iron sleeves and stainless steel valves. Compact and lightweight design. Manual reset overload protection. Equipped with regulator, pressure gauge, pressure switch with on/off, and manifold with universal couplers. CSA approved. Factory tested prior to shipment. 1-year limited manufacturer's warranty. Suitable for professional, farm, home and hobbyist use; not intended for industrial applications.
PN-1004L	115V/1PH	1	Oil-less direct drive air compressor. Maintenance-free operation. Die-cast aluminum pump with cast iron sleeves and stainless steel valves. Compact and lightweight design. Manual reset overload protection. Equipped with regulator, pressure gauge, pressure switch with on/off, and manifold with universal couplers. CSA approved. Factory tested prior to shipment. 1-year limited manufacturer's warranty. Suitable for professional, farm, home and hobbyist use; not intended for industrial applications.
LA-5702	115V/1PH	1.5	Oil-less direct drive air compressor. Maintenance-free operation. Die-cast aluminum pump with cast iron sleeves and stainless steel valves. Compact and lightweight design. Manual reset overload protection. Equipped with regulator, pressure gauge, pressure switch with on/off, and manifold with universal couplers. CSA approved. Factory tested prior to shipment. 1-year limited manufacturer's warranty. Suitable for professional, farm, home and hobbyist use; not intended for industrial applications.
LA-5708	115V/1PH	1.5	Oil-less direct drive air compressor. Maintenance-free operation. Die-cast aluminum pump with cast iron sleeves and stainless steel valves. Compact and lightweight design. Manual reset overload protection. Equipped with regulator, pressure gauge, pressure switch with on/off, and manifold with universal couplers. CSA approved. Factory tested prior to shipment. 1-year limited manufacturer's warranty. Suitable for professional, farm, home and hobbyist use; not intended for industrial applications.
LA-5721	115V/1PH	1.5	Oil-less direct drive air compressor. Maintenance-free operation. Die-cast aluminum pump with cast iron sleeves and stainless steel valves. Compact and lightweight design. Manual reset overload protection. Equipped with regulator, pressure gauge, pressure switch with on/off, and manifold with universal couplers. CSA approved. Factory tested prior to shipment. 1-year limited manufacturer's warranty. Suitable for professional, farm, home and hobbyist use; not intended for industrial applications.
MA-9004	115V/1PH	1.5	Oil-less direct drive air compressor. Maintenance-free operation. Die-cast aluminum pump with cast iron sleeves and stainless steel valves. Compact and lightweight design. Manual reset overload protection. Equipped with regulator, pressure gauge, pressure switch with on/off, and manifold with universal couplers. CSA approved. Factory tested prior to shipment. 1-year limited manufacturer's warranty. Suitable for professional, farm, home and hobbyist use; not intended for industrial applications.

## CONTRACTOR - OIL LUBE DIRECT DRIVE SERIES - 1720 RPM

MODEL NO.	VOLTAGE	HP	DESCRIPTION
DD-1004	115V/1PH	1	Oil-lubricated direct drive air compressor, 1720 RPM. Die-cast aluminum pump with cast iron sleeves and stainless steel valves. Compact and lightweight design. Manual reset overload protection. Equipped with regulator, pressure gauge, pressure switch with on/off, and manifold with universal couplers. Filter silencer with replacement filter element included. CSA approved. Factory tested prior to shipment. 1-year limited manufacturer's warranty.

<b>DD-1503</b>	<b>115V/1PH</b>	<b>1.5</b>	Oil-lubricated direct drive air compressor, 1720 RPM. Die-cast aluminum pump with cast iron sleeves and stainless steel valves. Compact and lightweight design. Manual reset overload protection. Equipped with regulator, pressure gauge, pressure switch with on/off, and manifold with universal couplers. Filter silencer with replacement filter element included. CSA approved. Factory tested prior to shipment. 1-year limited manufacturer's warranty.
<b>DD-2004V</b>	<b>115V/1PH</b>	<b>2</b>	Oil-lubricated direct drive air compressor, 1720 RPM. Die-cast aluminum pump with cast iron sleeves and stainless steel valves. Compact and lightweight design. Manual reset overload protection. Equipped with regulator, pressure gauge, pressure switch with on/off, and manifold with universal couplers. Filter silencer with replacement filter element included. CSA approved. Factory tested prior to shipment. 1-year limited manufacturer's warranty.
<b>DD-2008</b>	<b>115V/1PH</b>	<b>2</b>	Oil-lubricated direct drive air compressor, 1720 RPM. Die-cast aluminum pump with cast iron sleeves and stainless steel valves. Compact and lightweight design. Manual reset overload protection. Equipped with regulator, pressure gauge, pressure switch with on/off, and manifold with universal couplers. Filter silencer with replacement filter element included. CSA approved. Factory tested prior to shipment. 1-year limited manufacturer's warranty.
<b>DD-2022B</b>	<b>115V/1PH</b>	<b>2</b>	Oil-lubricated direct drive air compressor, 1720 RPM. Die-cast aluminum pump with cast iron sleeves and stainless steel valves. Compact and lightweight design. Manual reset overload protection. Equipped with regulator, pressure gauge, pressure switch with on/off, and manifold with universal couplers. Filter silencer with replacement filter element included. CSA approved. Factory tested prior to shipment. 1-year limited manufacturer's warranty.
<b>DD-2022HP</b>	<b>115V/1PH</b>	<b>2</b>	Oil-lubricated direct drive air compressor, 1720 RPM. Die-cast aluminum pump with cast iron sleeves and stainless steel valves. Compact and lightweight design. Manual reset overload protection. Equipped with regulator, pressure gauge, pressure switch with on/off, and manifold with universal couplers. Filter silencer with replacement filter element included. CSA approved. Factory tested prior to shipment. 1-year limited manufacturer's warranty.
<b>DD-2022S</b>	<b>115V/1PH</b>	<b>2</b>	Oil-lubricated direct drive air compressor, 1720 RPM. Die-cast aluminum pump with cast iron sleeves and stainless steel valves. Compact and lightweight design. Manual reset overload protection. Equipped with regulator, pressure gauge, pressure switch with on/off, and manifold with universal couplers. Filter silencer with replacement filter element included. CSA approved. Factory tested prior to shipment. 1-year limited manufacturer's warranty.
<b>DD-3008</b>	<b>115V/1PH</b>	<b>3</b>	Oil-lubricated direct drive air compressor, 1720 RPM. Die-cast aluminum pump with cast iron sleeves and stainless steel valves. Compact and lightweight design. Manual reset overload protection. Equipped with regulator, pressure gauge, pressure switch with on/off, and manifold with universal couplers. Filter silencer with replacement filter element included. CSA approved. Factory tested prior to shipment. 1-year limited manufacturer's warranty.

## CONTRACTOR - OIL LUBE DIRECT DRIVE SERIES - 3450 RPM

MODEL NO.	VOLTAGE	HP	DESCRIPTION
<b>ND-1003</b>	<b>115V/1PH</b>	<b>1</b>	Oil-lubricated direct drive air compressor, 3450 RPM. Die-cast aluminum pump with cast iron sleeves and stainless steel valves. Compact and lightweight design. Manual reset overload protection. Equipped with regulator, pressure gauge, pressure switch with on/off, and manifold with universal couplers. Filter silencer with replacement filter element included. CSA approved. Factory tested prior to shipment. 1-year limited manufacturer's warranty.

<b>DP-2004V</b>	<b>115V/1PH</b>	<b>2</b>	Oil-lubricated direct drive air compressor, 3450 RPM. Die-cast aluminum pump with cast iron sleeves and stainless steel valves. Compact and lightweight design. Manual reset overload protection. Equipped with regulator, pressure gauge, pressure switch with on/off, and manifold with universal couplers. Filter silencer with replacement filter element included. CSA approved. Factory tested prior to shipment. 1-year limited manufacturer's warranty.
<b>DP-2022S</b>	<b>115V/1PH</b>	<b>2</b>	Oil-lubricated direct drive air compressor, 3450 RPM. Die-cast aluminum pump with cast iron sleeves and stainless steel valves. Compact and lightweight design. Manual reset overload protection. Equipped with regulator, pressure gauge, pressure switch with on/off, and manifold with universal couplers. Filter silencer with replacement filter element included. CSA approved. Factory tested prior to shipment. 1-year limited manufacturer's warranty.
<b>DP-2022W</b>	<b>115V/1PH</b>	<b>2</b>	Oil-lubricated direct drive air compressor, 3450 RPM. Die-cast aluminum pump with cast iron sleeves and stainless steel valves. Compact and lightweight design. Manual reset overload protection. Equipped with regulator, pressure gauge, pressure switch with on/off, and manifold with universal couplers. Filter silencer with replacement filter element included. CSA approved. Factory tested prior to shipment. 1-year limited manufacturer's warranty.
<b>DP-3008</b>	<b>115V/1PH</b>	<b>3</b>	Oil-lubricated direct drive air compressor, 3450 RPM. Die-cast aluminum pump with cast iron sleeves and stainless steel valves. Compact and lightweight design. Manual reset overload protection. Equipped with regulator, pressure gauge, pressure switch with on/off, and manifold with universal couplers. Filter silencer with replacement filter element included. CSA approved. Factory tested prior to shipment. 1-year limited manufacturer's warranty.

## CONTRACTOR - BELT DRIVEN AND GAS OUTFITS

<b>MODEL NO.</b>	<b>VOLTAGE</b>	<b>HP</b>	<b>DESCRIPTION</b>
<b>PUK-1508MDC</b>	<b>115V/1PH</b>	<b>1.5</b>	Belt driven electric or Honda gas engine belt driven air compressor. Compact portable design with dual control. Equipped with regulator, pressure gauge, and pressure switch. CSA approved (electric models). Factory tested prior to shipment. 1-year limited manufacturer's warranty.
<b>PUK-1520MDC</b>	<b>115V/1PH</b>	<b>1.5</b>	Belt driven electric or Honda gas engine belt driven air compressor. Compact portable design with dual control. Equipped with regulator, pressure gauge, and pressure switch. CSA approved (electric models). Factory tested prior to shipment. 1-year limited manufacturer's warranty.
<b>PUK-2008MDC</b>	<b>115V/1PH</b>	<b>2</b>	Belt driven electric or Honda gas engine belt driven air compressor. Compact portable design with dual control. Equipped with regulator, pressure gauge, and pressure switch. CSA approved (electric models). Factory tested prior to shipment. 1-year limited manufacturer's warranty.
<b>PUK-2020MDC</b>	<b>115V/1PH</b>	<b>2</b>	Belt driven electric or Honda gas engine belt driven air compressor. Compact portable design with dual control. Equipped with regulator, pressure gauge, and pressure switch. CSA approved (electric models). Factory tested prior to shipment. 1-year limited manufacturer's warranty.
<b>DG-5522HP</b>	<b>N/A (Gas)</b>	<b>5.5</b>	Belt driven electric or Honda gas engine belt driven air compressor. Compact portable design with dual control. Equipped with regulator, pressure gauge, and pressure switch. CSA approved (electric models). Factory tested prior to shipment. 1-year limited manufacturer's warranty.
<b>PUK-5508G</b>	<b>N/A (Gas)</b>	<b>5.5</b>	Belt driven electric or Honda gas engine belt driven air compressor. Compact portable design with dual control. Equipped with regulator, pressure gauge, and pressure switch. CSA approved (electric models). Factory tested prior to shipment. 1-year limited manufacturer's warranty.

<b>PUK-5520G</b>	<b>N/A (Gas)</b>	<b>5.5</b>	Belt driven electric or Honda gas engine belt driven air compressor. Compact portable design with dual control. Equipped with regulator, pressure gauge, and pressure switch. CSA approved (electric models). Factory tested prior to shipment. 1-year limited manufacturer's warranty.
<b>PUK-6508G</b>	<b>N/A (Gas)</b>	<b>6.5</b>	Belt driven electric or Honda gas engine belt driven air compressor. Compact portable design with dual control. Equipped with regulator, pressure gauge, and pressure switch. CSA approved (electric models). Factory tested prior to shipment. 1-year limited manufacturer's warranty.
<b>PUK-6520G</b>	<b>N/A (Gas)</b>	<b>6.5</b>	Belt driven electric or Honda gas engine belt driven air compressor. Compact portable design with dual control. Equipped with regulator, pressure gauge, and pressure switch. CSA approved (electric models). Factory tested prior to shipment. 1-year limited manufacturer's warranty.
<b>PUK-8008GE</b>	<b>N/A (Gas)</b>	<b>8</b>	Belt driven electric or Honda gas engine belt driven air compressor. Compact portable design with dual control. Equipped with regulator, pressure gauge, and pressure switch. CSA approved (electric models). Factory tested prior to shipment. 1-year limited manufacturer's warranty.
<b>PUK-9008G</b>	<b>N/A (Gas)</b>	<b>9</b>	Belt driven electric or Honda gas engine belt driven air compressor. Compact portable design with dual control. Equipped with regulator, pressure gauge, and pressure switch. CSA approved (electric models). Factory tested prior to shipment. 1-year limited manufacturer's warranty.
<b>PUK-9020G</b>	<b>N/A (Gas)</b>	<b>9</b>	Belt driven electric or Honda gas engine belt driven air compressor. Compact portable design with dual control. Equipped with regulator, pressure gauge, and pressure switch. CSA approved (electric models). Factory tested prior to shipment. 1-year limited manufacturer's warranty.
<b>TUE-8008GE</b>	<b>N/A (Gas)</b>	<b>8</b>	Belt driven electric or Honda gas engine belt driven air compressor. Compact portable design with dual control. Equipped with regulator, pressure gauge, and pressure switch. CSA approved (electric models). Factory tested prior to shipment. 1-year limited manufacturer's warranty.

## PROFESSIONAL SERIES

<b>MODEL NO.</b>	<b>VOLTAGE</b>	<b>HP</b>	<b>DESCRIPTION</b>
<b>PK-2008</b>	<b>115V/1PH</b>	<b>2</b>	Belt driven professional series air compressor. Die-cast aluminum pump with cast iron sleeves and stainless steel valves for extended durability. Compact portable design. CSA approved. Factory tested prior to shipment. 1-year limited manufacturer's warranty.
<b>PK-3011</b>	<b>115V/1PH</b>	<b>3</b>	Belt driven professional series air compressor. Die-cast aluminum pump with cast iron sleeves and stainless steel valves for extended durability. Compact portable design. CSA approved. Factory tested prior to shipment. 1-year limited manufacturer's warranty.
<b>PK-5020</b>	<b>115V/1PH</b>	<b>5</b>	Belt driven professional series air compressor. Die-cast aluminum pump with cast iron sleeves and stainless steel valves for extended durability. Compact portable design. CSA approved. Factory tested prior to shipment. 1-year limited manufacturer's warranty.
<b>PK-5020VP</b>	<b>115V/1PH</b>	<b>5</b>	Belt driven professional series air compressor. Die-cast aluminum pump with cast iron sleeves and stainless steel valves for extended durability. Compact portable design. CSA approved. Factory tested prior to shipment. 1-year limited manufacturer's warranty.

PP-6060V	230V/1PH	6	Belt driven professional series air compressor. Die-cast aluminum pump with cast iron sleeves and stainless steel valves for extended durability. Compact portable design. CSA approved. Factory tested prior to shipment. 1-year limited manufacturer's warranty.
PK-6560V	230V/1PH	6.5	Belt driven professional series air compressor. Die-cast aluminum pump with cast iron sleeves and stainless steel valves for extended durability. Compact portable design. CSA approved. Factory tested prior to shipment. 1-year limited manufacturer's warranty.

## HEAVY DUTY INDUSTRIAL SERIES - SIMPLEX TANK MOUNTED SERIES

MODEL NO.	VOLTAGE	HP	DESCRIPTION
TE-5060-01	230V/1PH	5	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
TE-5060-01M	230V/1PH	5	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
TE-5060-010M	230V/1PH	5	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
TE-5060V-01	230V/1PH	5	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
TE-5060V-01M	230V/1PH	5	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
TE-5060V-010M	230V/1PH	5	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).

<b>TE-5080-01</b>	<b>230V/1PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TE-5080-01M</b>	<b>230V/1PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TE-5080-010M</b>	<b>230V/1PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TE-5080V-01</b>	<b>230V/1PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TE-5080V-01M</b>	<b>230V/1PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TE-5080V-010M</b>	<b>230V/1PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-5060-01</b>	<b>230V/1PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-5060-01M</b>	<b>230V/1PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).

<b>TK-5060-01OM</b>	<b>230V/1PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-5060-02</b>	<b>200-208V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-5060-02M</b>	<b>200-208V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-5060-02OM</b>	<b>200-208V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-5060-03</b>	<b>230-240V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-5060-03M</b>	<b>230-240V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-5060-03OM</b>	<b>230-240V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-5060-04</b>	<b>460-480V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).

<b>TK-5060-04M</b>	<b>460-480V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-5060-040M</b>	<b>460-480V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-5060-05</b>	<b>575-600V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-5060-05M</b>	<b>575-600V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-5060-050M</b>	<b>575-600V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-5060V-01</b>	<b>230V/1PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-5060V-01M</b>	<b>230V/1PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-5060V-010M</b>	<b>230V/1PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).

<b>TK-5060V-02</b>	<b>200-208V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-5060V-02M</b>	<b>200-208V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-5060V-02OM</b>	<b>200-208V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-5060V-03</b>	<b>230-240V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-5060V-03M</b>	<b>230-240V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-5060V-03OM</b>	<b>230-240V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-5060V-04</b>	<b>460-480V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-5060V-04M</b>	<b>460-480V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).

<b>TK-5060V-040M</b>	<b>460-480V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-5060V-05</b>	<b>575-600V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-5060V-05M</b>	<b>575-600V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-5060V-050M</b>	<b>575-600V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-5080-01</b>	<b>230V/1PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-5080-01M</b>	<b>230V/1PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-5080-010M</b>	<b>230V/1PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-5080-02</b>	<b>200-208V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).

<b>TK-5080-02M</b>	<b>200-208V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-5080-02OM</b>	<b>200-208V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-5080-03</b>	<b>230-240V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-5080-03M</b>	<b>230-240V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-5080-03OM</b>	<b>230-240V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-5080-04</b>	<b>460-480V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-5080-04M</b>	<b>460-480V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-5080-04OM</b>	<b>460-480V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).

<b>TK-5080-05</b>	<b>575-600V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-5080-05M</b>	<b>575-600V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-5080-05OM</b>	<b>575-600V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-5080V-01</b>	<b>230V/1PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-5080V-01M</b>	<b>230V/1PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-5080V-01OM</b>	<b>230V/1PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-5080V-02</b>	<b>200-208V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-5080V-02M</b>	<b>200-208V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).

<b>TK-5080V-020M</b>	<b>200-208V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-5080V-03</b>	<b>230-240V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-5080V-03M</b>	<b>230-240V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-5080V-030M</b>	<b>230-240V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-5080V-04</b>	<b>460-480V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-5080V-04M</b>	<b>460-480V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-5080V-040M</b>	<b>460-480V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-5080V-05</b>	<b>575-600V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).

<b>TK-5080V-05M</b>	<b>575-600V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-5080V-050M</b>	<b>575-600V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-50120-01</b>	<b>230V/1PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-50120-01M</b>	<b>230V/1PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-50120-010M</b>	<b>230V/1PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-50120-02</b>	<b>200-208V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-50120-02M</b>	<b>200-208V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-50120-020M</b>	<b>200-208V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).

<b>TK-50120-03</b>	<b>230-240V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-50120-03M</b>	<b>230-240V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-50120-03OM</b>	<b>230-240V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-50120-04</b>	<b>460-480V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-50120-04M</b>	<b>460-480V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-50120-04OM</b>	<b>460-480V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-50120-05</b>	<b>575-600V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-50120-05M</b>	<b>575-600V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).

<b>TK-50120-050M</b>	<b>575-600V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-50120V-01</b>	<b>230V/1PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-50120V-01M</b>	<b>230V/1PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-50120V-010M</b>	<b>230V/1PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-50120V-02</b>	<b>200-208V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-50120V-02M</b>	<b>200-208V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-50120V-020M</b>	<b>200-208V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-50120V-03</b>	<b>230-240V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).

<b>TK-50120V-03M</b>	<b>230-240V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-50120V-030M</b>	<b>230-240V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-50120V-04</b>	<b>460-480V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-50120V-04M</b>	<b>460-480V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-50120V-040M</b>	<b>460-480V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-50120V-05</b>	<b>575-600V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-50120V-05M</b>	<b>575-600V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-50120V-050M</b>	<b>575-600V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).

<b>TK-7580-01</b>	<b>230V/1PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-7580-01M</b>	<b>230V/1PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-7580-01OM</b>	<b>230V/1PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-7580-02</b>	<b>200-208V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-7580-02M</b>	<b>200-208V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-7580-02OM</b>	<b>200-208V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-7580-03</b>	<b>230-240V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-7580-03M</b>	<b>230-240V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).

<b>TK-7580-03OM</b>	<b>230-240V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-7580-04</b>	<b>460-480V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-7580-04M</b>	<b>460-480V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-7580-04OM</b>	<b>460-480V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-7580-05</b>	<b>575-600V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-7580-05M</b>	<b>575-600V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-7580-05OM</b>	<b>575-600V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-7580V-01</b>	<b>230V/1PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).

<b>TK-7580V-01M</b>	<b>230V/1PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-7580V-010M</b>	<b>230V/1PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-7580V-02</b>	<b>200-208V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-7580V-02M</b>	<b>200-208V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-7580V-020M</b>	<b>200-208V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-7580V-03</b>	<b>230-240V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-7580V-03M</b>	<b>230-240V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-7580V-030M</b>	<b>230-240V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).

<b>TK-7580V-04</b>	<b>460-480V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-7580V-04M</b>	<b>460-480V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-7580V-04OM</b>	<b>460-480V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-7580V-05</b>	<b>575-600V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-7580V-05M</b>	<b>575-600V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-7580V-05OM</b>	<b>575-600V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-75120-01</b>	<b>230V/1PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-75120-01M</b>	<b>230V/1PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).

<b>TK-75120-010M</b>	<b>230V/1PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-75120-02</b>	<b>200-208V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-75120-02M</b>	<b>200-208V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-75120-020M</b>	<b>200-208V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-75120-03</b>	<b>230-240V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-75120-03M</b>	<b>230-240V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-75120-030M</b>	<b>230-240V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-75120-04</b>	<b>460-480V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).

<b>TK-75120-04M</b>	<b>460-480V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-75120-040M</b>	<b>460-480V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-75120-05</b>	<b>575-600V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-75120-05M</b>	<b>575-600V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-75120-050M</b>	<b>575-600V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-75120V-01</b>	<b>230V/1PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-75120V-01M</b>	<b>230V/1PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-75120V-010M</b>	<b>230V/1PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).

<b>TK-75120V-02</b>	<b>200-208V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-75120V-02M</b>	<b>200-208V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-75120V-020M</b>	<b>200-208V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-75120V-03</b>	<b>230-240V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-75120V-03M</b>	<b>230-240V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-75120V-030M</b>	<b>230-240V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-75120V-04</b>	<b>460-480V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-75120V-04M</b>	<b>460-480V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).

<b>TK-75120V-040M</b>	<b>460-480V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-75120V-05</b>	<b>575-600V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-75120V-05M</b>	<b>575-600V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-75120V-050M</b>	<b>575-600V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-10080-01</b>	<b>230V/1PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-10080-01M</b>	<b>230V/1PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-10080-02</b>	<b>200-208V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-10080-02M</b>	<b>200-208V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).

<b>TK-10080-02OM</b>	<b>200-208V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-10080-03</b>	<b>230-240V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-10080-03M</b>	<b>230-240V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-10080-03OM</b>	<b>230-240V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-10080-04</b>	<b>460-480V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-10080-04M</b>	<b>460-480V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-10080-04OM</b>	<b>460-480V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-10080-05</b>	<b>575-600V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).

<b>TK-10080-05M</b>	<b>575-600V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-10080-050M</b>	<b>575-600V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-10080V-01</b>	<b>230V/1PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-10080V-01M</b>	<b>230V/1PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-10080V-02</b>	<b>200-208V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-10080V-02M</b>	<b>200-208V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-10080V-020M</b>	<b>200-208V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-10080V-03</b>	<b>230-240V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).

<b>TK-10080V-03M</b>	<b>230-240V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-10080V-030M</b>	<b>230-240V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-10080V-04</b>	<b>460-480V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-10080V-04M</b>	<b>460-480V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-10080V-040M</b>	<b>460-480V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-10080V-05</b>	<b>575-600V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-10080V-05M</b>	<b>575-600V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-10080V-050M</b>	<b>575-600V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).

<b>TK-100120-01</b>	<b>230V/1PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-100120-01M</b>	<b>230V/1PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-100120-02</b>	<b>200-208V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-100120-02M</b>	<b>200-208V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-100120-02OM</b>	<b>200-208V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-100120-03</b>	<b>230-240V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-100120-03M</b>	<b>230-240V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-100120-03OM</b>	<b>230-240V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).

<b>TK-100120-04</b>	<b>460-480V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-100120-04M</b>	<b>460-480V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-100120-040M</b>	<b>460-480V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-100120-05</b>	<b>575-600V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-100120-05M</b>	<b>575-600V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-100120-050M</b>	<b>575-600V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-100120V-01</b>	<b>230V/1PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-100120V-01M</b>	<b>230V/1PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).

<b>TK-100120V-02</b>	<b>200-208V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-100120V-02M</b>	<b>200-208V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-100120V-02OM</b>	<b>200-208V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-100120V-03</b>	<b>230-240V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-100120V-03M</b>	<b>230-240V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-100120V-03OM</b>	<b>230-240V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-100120V-04</b>	<b>460-480V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-100120V-04M</b>	<b>460-480V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).

<b>TK-100120V-040M</b>	<b>460-480V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-100120V-05</b>	<b>575-600V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-100120V-05M</b>	<b>575-600V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-100120V-050M</b>	<b>575-600V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-100240-01</b>	<b>230V/1PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-100240-01M</b>	<b>230V/1PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-100240-02</b>	<b>200-208V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-100240-02M</b>	<b>200-208V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).

<b>TK-100240-02OM</b>	<b>200-208V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-100240-03</b>	<b>230-240V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-100240-03M</b>	<b>230-240V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-100240-03OM</b>	<b>230-240V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-100240-04</b>	<b>460-480V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-100240-04M</b>	<b>460-480V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-100240-04OM</b>	<b>460-480V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-100240-05</b>	<b>575-600V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).

<b>TK-100240-05M</b>	<b>575-600V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-100240-050M</b>	<b>575-600V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-150120-02</b>	<b>200-208V/3PH</b>	<b>15</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-150120-02M</b>	<b>200-208V/3PH</b>	<b>15</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-150120-020M</b>	<b>200-208V/3PH</b>	<b>15</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-150120-03</b>	<b>230-240V/3PH</b>	<b>15</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-150120-03M</b>	<b>230-240V/3PH</b>	<b>15</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-150120-030M</b>	<b>230-240V/3PH</b>	<b>15</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).

<b>GT-150120-04</b>	<b>460-480V/3PH</b>	<b>15</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-150120-04M</b>	<b>460-480V/3PH</b>	<b>15</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-150120-040M</b>	<b>460-480V/3PH</b>	<b>15</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-150120-05</b>	<b>575-600V/3PH</b>	<b>15</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-150120-05M</b>	<b>575-600V/3PH</b>	<b>15</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-150120-050M</b>	<b>575-600V/3PH</b>	<b>15</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-150120V-02</b>	<b>200-208V/3PH</b>	<b>15</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-150120V-02M</b>	<b>200-208V/3PH</b>	<b>15</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).

<b>GT-150120V-020M</b>	<b>200-208V/3PH</b>	<b>15</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-150120V-03</b>	<b>230-240V/3PH</b>	<b>15</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-150120V-03M</b>	<b>230-240V/3PH</b>	<b>15</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-150120V-030M</b>	<b>230-240V/3PH</b>	<b>15</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-150120V-04</b>	<b>460-480V/3PH</b>	<b>15</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-150120V-04M</b>	<b>460-480V/3PH</b>	<b>15</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-150120V-040M</b>	<b>460-480V/3PH</b>	<b>15</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-150120V-05</b>	<b>575-600V/3PH</b>	<b>15</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).

<b>GT-150120V-05M</b>	<b>575-600V/3PH</b>	<b>15</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-150120V-050M</b>	<b>575-600V/3PH</b>	<b>15</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-150240-02</b>	<b>200-208V/3PH</b>	<b>15</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-150240-02M</b>	<b>200-208V/3PH</b>	<b>15</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-150240-020M</b>	<b>200-208V/3PH</b>	<b>15</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-150240-03</b>	<b>230-240V/3PH</b>	<b>15</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-150240-03M</b>	<b>230-240V/3PH</b>	<b>15</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-150240-030M</b>	<b>230-240V/3PH</b>	<b>15</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).

<b>GT-150240-04</b>	<b>460-480V/3PH</b>	<b>15</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-150240-04M</b>	<b>460-480V/3PH</b>	<b>15</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-150240-040M</b>	<b>460-480V/3PH</b>	<b>15</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-150240-05</b>	<b>575-600V/3PH</b>	<b>15</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-150240-05M</b>	<b>575-600V/3PH</b>	<b>15</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-150240-050M</b>	<b>575-600V/3PH</b>	<b>15</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-200120-02</b>	<b>200-208V/3PH</b>	<b>20</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-200120-02M</b>	<b>200-208V/3PH</b>	<b>20</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).

<b>GT-200120-020M</b>	<b>200-208V/3PH</b>	<b>20</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-200120-03</b>	<b>230-240V/3PH</b>	<b>20</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-200120-03M</b>	<b>230-240V/3PH</b>	<b>20</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-200120-030M</b>	<b>230-240V/3PH</b>	<b>20</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-200120-04</b>	<b>460-480V/3PH</b>	<b>20</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-200120-04M</b>	<b>460-480V/3PH</b>	<b>20</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-200120-040M</b>	<b>460-480V/3PH</b>	<b>20</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-200120-05</b>	<b>575-600V/3PH</b>	<b>20</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).

<b>GT-200120-05M</b>	<b>575-600V/3PH</b>	<b>20</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-200120-050M</b>	<b>575-600V/3PH</b>	<b>20</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-200120V-02</b>	<b>200-208V/3PH</b>	<b>20</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-200120V-02M</b>	<b>200-208V/3PH</b>	<b>20</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-200120V-020M</b>	<b>200-208V/3PH</b>	<b>20</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-200120V-03</b>	<b>230-240V/3PH</b>	<b>20</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-200120V-03M</b>	<b>230-240V/3PH</b>	<b>20</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-200120V-030M</b>	<b>230-240V/3PH</b>	<b>20</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).

<b>GT-200120V-04</b>	<b>460-480V/3PH</b>	<b>20</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-200120V-04M</b>	<b>460-480V/3PH</b>	<b>20</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-200120V-04OM</b>	<b>460-480V/3PH</b>	<b>20</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-200120V-05</b>	<b>575-600V/3PH</b>	<b>20</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-200120V-05M</b>	<b>575-600V/3PH</b>	<b>20</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-200120V-05OM</b>	<b>575-600V/3PH</b>	<b>20</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-200240-02</b>	<b>200-208V/3PH</b>	<b>20</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-200240-02M</b>	<b>200-208V/3PH</b>	<b>20</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).

<b>GT-200240-020M</b>	<b>200-208V/3PH</b>	<b>20</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-200240-03</b>	<b>230-240V/3PH</b>	<b>20</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-200240-03M</b>	<b>230-240V/3PH</b>	<b>20</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-200240-030M</b>	<b>230-240V/3PH</b>	<b>20</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-200240-04</b>	<b>460-480V/3PH</b>	<b>20</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-200240-04M</b>	<b>460-480V/3PH</b>	<b>20</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-200240-040M</b>	<b>460-480V/3PH</b>	<b>20</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-200240-05</b>	<b>575-600V/3PH</b>	<b>20</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).

<b>GT-200240-05M</b>	<b>575-600V/3PH</b>	<b>20</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-200240-050M</b>	<b>575-600V/3PH</b>	<b>20</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-250240-02</b>	<b>200-208V/3PH</b>	<b>25</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-250240-02M</b>	<b>200-208V/3PH</b>	<b>25</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-250240-020M</b>	<b>200-208V/3PH</b>	<b>25</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-250240-03</b>	<b>230-240V/3PH</b>	<b>25</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-250240-03M</b>	<b>230-240V/3PH</b>	<b>25</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-250240-030M</b>	<b>230-240V/3PH</b>	<b>25</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).

<b>TK-250240-04</b>	<b>460-480V/3PH</b>	<b>25</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-250240-04M</b>	<b>460-480V/3PH</b>	<b>25</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-250240-040M</b>	<b>460-480V/3PH</b>	<b>25</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-250240-05</b>	<b>575-600V/3PH</b>	<b>25</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-250240-05M</b>	<b>575-600V/3PH</b>	<b>25</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-250240-050M</b>	<b>575-600V/3PH</b>	<b>25</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-300240-02</b>	<b>200-208V/3PH</b>	<b>30</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-300240-02M</b>	<b>200-208V/3PH</b>	<b>30</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).

<b>TK-300240-02OM</b>	<b>200-208V/3PH</b>	<b>30</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-300240-03</b>	<b>230-240V/3PH</b>	<b>30</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-300240-03M</b>	<b>230-240V/3PH</b>	<b>30</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-300240-03OM</b>	<b>230-240V/3PH</b>	<b>30</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-300240-04</b>	<b>460-480V/3PH</b>	<b>30</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-300240-04M</b>	<b>460-480V/3PH</b>	<b>30</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-300240-04OM</b>	<b>460-480V/3PH</b>	<b>30</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-300240-05</b>	<b>575-600V/3PH</b>	<b>30</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).

<b>TK-300240-05M</b>	<b>575-600V/3PH</b>	<b>30</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-300240-050M</b>	<b>575-600V/3PH</b>	<b>30</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler, dual control (start/stop and continuous run).

## HEAVY DUTY INDUSTRIAL SERIES - BASE MOUNTED SERIES

MODEL NO.	VOLTAGE	HP	DESCRIPTION
<b>TE-5000-01</b>	<b>230V/1PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>TE-5000-01M</b>	<b>230V/1PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>TE-5000-010M</b>	<b>230V/1PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-5000-01</b>	<b>230V/1PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-5000-01M</b>	<b>230V/1PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).

<b>TK-5000-01OM</b>	<b>230V/1PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-5000-02</b>	<b>200-208V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-5000-02M</b>	<b>200-208V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-5000-02OM</b>	<b>200-208V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-5000-03</b>	<b>230-240V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-5000-03M</b>	<b>230-240V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-5000-03OM</b>	<b>230-240V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-5000-04</b>	<b>460-480V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).

<b>TK-5000-04M</b>	<b>460-480V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-5000-040M</b>	<b>460-480V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-5000-05</b>	<b>575-600V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-5000-05M</b>	<b>575-600V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-5000-050M</b>	<b>575-600V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-7500-01</b>	<b>230V/1PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-7500-01M</b>	<b>230V/1PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-7500-010M</b>	<b>230V/1PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).

<b>TK-7500-02</b>	<b>200-208V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-7500-02M</b>	<b>200-208V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-7500-02OM</b>	<b>200-208V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-7500-03</b>	<b>230-240V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-7500-03M</b>	<b>230-240V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-7500-03OM</b>	<b>230-240V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-7500-04</b>	<b>460-480V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-7500-04M</b>	<b>460-480V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).

<b>TK-7500-040M</b>	<b>460-480V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-7500-05</b>	<b>575-600V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-7500-05M</b>	<b>575-600V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-7500-050M</b>	<b>575-600V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-100000-01</b>	<b>230V/1PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-100000-01M</b>		<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-100000-02</b>	<b>200-208V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-100000-02M</b>	<b>200-208V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).

<b>TK-100000-020M</b>	<b>200-208V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-100000-03</b>	<b>230-240V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-100000-03M</b>	<b>230-240V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-100000-030M</b>	<b>230-240V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-100000-04</b>	<b>460-480V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-100000-04M</b>	<b>460-480V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-100000-040M</b>	<b>460-480V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-100000-05</b>	<b>575-600V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).

<b>TK-100000-05M</b>	<b>575-600V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-100000-050M</b>	<b>575-600V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-150000-02</b>	<b>200-208V/3PH</b>	<b>15</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-150000-02M</b>	<b>200-208V/3PH</b>	<b>15</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-150000-020M</b>	<b>200-208V/3PH</b>	<b>15</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-150000-03</b>	<b>230-240V/3PH</b>	<b>15</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-150000-03M</b>	<b>230-240V/3PH</b>	<b>15</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-150000-030M</b>	<b>230-240V/3PH</b>	<b>15</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).

<b>GT-150000-04</b>	<b>460-480V/3PH</b>	<b>15</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-150000-04M</b>	<b>460-480V/3PH</b>	<b>15</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-150000-040M</b>	<b>460-480V/3PH</b>	<b>15</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-150000-05</b>	<b>575-600V/3PH</b>	<b>15</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-150000-05M</b>	<b>575-600V/3PH</b>	<b>15</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-150000-050M</b>	<b>575-600V/3PH</b>	<b>15</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-200000-02</b>	<b>200-208V/3PH</b>	<b>20</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-200000-02M</b>	<b>200-208V/3PH</b>	<b>20</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).

<b>GT-200000-020M</b>	<b>200-208V/3PH</b>	<b>20</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-200000-03</b>	<b>230-240V/3PH</b>	<b>20</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-200000-03M</b>	<b>230-240V/3PH</b>	<b>20</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-200000-030M</b>	<b>230-240V/3PH</b>	<b>20</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-200000-04</b>	<b>460-480V/3PH</b>	<b>20</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-200000-04M</b>	<b>460-480V/3PH</b>	<b>20</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-200000-040M</b>	<b>460-480V/3PH</b>	<b>20</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-200000-05</b>	<b>575-600V/3PH</b>	<b>20</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).

<b>GT-200000-05M</b>	<b>575-600V/3PH</b>	<b>20</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>GT-200000-050M</b>	<b>575-600V/3PH</b>	<b>20</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-250000-02</b>	<b>200-208V/3PH</b>	<b>25</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-250000-02M</b>	<b>200-208V/3PH</b>	<b>25</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-250000-020M</b>	<b>200-208V/3PH</b>	<b>25</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-250000-03</b>	<b>230-240V/3PH</b>	<b>25</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-250000-03M</b>	<b>230-240V/3PH</b>	<b>25</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-250000-030M</b>	<b>230-240V/3PH</b>	<b>25</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).

<b>TK-250000-04</b>	<b>460-480V/3PH</b>	<b>25</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-250000-04M</b>	<b>460-480V/3PH</b>	<b>25</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-250000-040M</b>	<b>460-480V/3PH</b>	<b>25</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-250000-05</b>	<b>575-600V/3PH</b>	<b>25</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-250000-05M</b>	<b>575-600V/3PH</b>	<b>25</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-250000-050M</b>	<b>575-600V/3PH</b>	<b>25</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-300000-02</b>	<b>200-208V/3PH</b>	<b>30</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-300000-02M</b>	<b>200-208V/3PH</b>	<b>30</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).

<b>TK-300000-020M</b>	<b>200-208V/3PH</b>	<b>30</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-300000-03</b>	<b>230-240V/3PH</b>	<b>30</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-300000-03M</b>	<b>230-240V/3PH</b>	<b>30</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-300000-030M</b>	<b>230-240V/3PH</b>	<b>30</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-300000-04</b>	<b>460-480V/3PH</b>	<b>30</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-300000-04M</b>	<b>460-480V/3PH</b>	<b>30</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-300000-040M</b>	<b>460-480V/3PH</b>	<b>30</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-300000-05</b>	<b>575-600V/3PH</b>	<b>30</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).

<b>TK-300000-05M</b>	<b>575-600V/3PH</b>	<b>30</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).
<b>TK-300000-050M</b>	<b>575-600V/3PH</b>	<b>30</b>	Heavy duty two stage high efficient cast iron air compressor. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler, dual control (start/stop and continuous run).

## HEAVY DUTY INDUSTRIAL SERIES - DUPLEX SERIES

<b>MODEL NO.</b>	<b>VOLTAGE</b>	<b>HP</b>	<b>DESCRIPTION</b>
<b>TK-DX-5080-01</b>	<b>230V/1PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-5080-01ALT</b>	<b>230V/1PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-5080-01OALT</b>	<b>230V/1PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-5080-02</b>	<b>200-208V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-5080-02ALT</b>	<b>200-208V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.

<b>TK-DX-5080-02OALT</b>	<b>200-208V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-5080-03</b>	<b>230-240V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-5080-03ALT</b>	<b>230-240V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-5080-03OALT</b>	<b>230-240V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-5080-04</b>	<b>460-480V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-5080-04ALT</b>	<b>460-480V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-5080-04OALT</b>	<b>460-480V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-5080-05</b>	<b>575-600V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.

<b>TK-DX-5080-05ALT</b>	<b>575-600V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-5080-05OALT</b>	<b>575-600V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-50120-01</b>	<b>230V/1PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-50120-01ALT</b>	<b>230V/1PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-50120-01OALT</b>	<b>230V/1PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-50120-02</b>	<b>200-208V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-50120-02ALT</b>	<b>200-208V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-50120-02OALT</b>	<b>200-208V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.

<b>TK-DX-50120-03</b>	<b>230-240V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-50120-03ALT</b>	<b>230-240V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-50120-03OALT</b>	<b>230-240V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-50120-04</b>	<b>460-480V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-50120-04ALT</b>	<b>460-480V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-50120-04OALT</b>	<b>460-480V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-50120-05</b>	<b>575-600V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-50120-05ALT</b>	<b>575-600V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.

<b>TK-DX-50120-050ALT</b>	<b>575-600V/3PH</b>	<b>5</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-75120-01</b>	<b>230V/1PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-75120-01ALT</b>	<b>230V/1PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-75120-010ALT</b>	<b>230V/1PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-75120-02</b>	<b>200-208V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-75120-02ALT</b>	<b>200-208V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-75120-020ALT</b>	<b>200-208V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-75120-03</b>	<b>230-240V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.

<b>TK-DX-75120-03ALT</b>	<b>230-240V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-75120-03OALT</b>	<b>230-240V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-75120-04</b>	<b>460-480V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-75120-04ALT</b>	<b>460-480V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-75120-04OALT</b>	<b>460-480V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-75120-05</b>	<b>575-600V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-75120-05ALT</b>	<b>575-600V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-75120-05OALT</b>	<b>575-600V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.

<b>TK-DX-75240-01</b>	<b>230V/1PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-75240-01ALT</b>	<b>230V/1PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-75240-01OALT</b>	<b>230V/1PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-75240-02</b>	<b>200-208V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-75240-02ALT</b>	<b>200-208V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-75240-02OALT</b>	<b>200-208V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-75240-03</b>	<b>230-240V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-75240-03ALT</b>	<b>230-240V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.

<b>TK-DX-75240-030ALT</b>	<b>230-240V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-75240-04</b>	<b>460-480V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-75240-04ALT</b>	<b>460-480V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-75240-040ALT</b>	<b>460-480V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-75240-05</b>	<b>575-600V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-75240-05ALT</b>	<b>575-600V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-75240-050ALT</b>	<b>575-600V/3PH</b>	<b>7.5</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-100120-01</b>	<b>230V/1PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.

<b>TK-DX-100120-01ALT</b>	<b>230V/1PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-100120-01OALT</b>	<b>230V/1PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-100120-02</b>	<b>200-208V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-100120-02ALT</b>	<b>200-208V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-100120-02OALT</b>	<b>200-208V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-100120-03</b>	<b>230-240V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-100120-03ALT</b>	<b>230-240V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-100120-03OALT</b>	<b>230-240V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.

<b>TK-DX-100120-04</b>	<b>460-480V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-100120-04ALT</b>	<b>460-480V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-100120-04OALT</b>	<b>460-480V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-100120-05</b>	<b>575-600V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-100120-05ALT</b>	<b>575-600V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-100120-05OALT</b>	<b>575-600V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-100240-01</b>	<b>230V/1PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-100240-01ALT</b>	<b>230V/1PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.

<b>TK-DX-100240-01OALT</b>	<b>230V/1PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-100240-02</b>	<b>200-208V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-100240-02ALT</b>	<b>200-208V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-100240-02OALT</b>	<b>200-208V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-100240-03</b>	<b>230-240V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-100240-03ALT</b>	<b>230-240V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-100240-03OALT</b>	<b>230-240V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-100240-04</b>	<b>460-480V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.

<b>TK-DX-100240-04ALT</b>	<b>460-480V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-100240-04OALT</b>	<b>460-480V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-100240-05</b>	<b>575-600V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-100240-05ALT</b>	<b>575-600V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>TK-DX-100240-05OALT</b>	<b>575-600V/3PH</b>	<b>10</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>GT-DX-150240-02</b>	<b>200-208V/3PH</b>	<b>15</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>GT-DX-150240-02ALT</b>	<b>200-208V/3PH</b>	<b>15</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>GT-DX-150240-02OALT</b>	<b>200-208V/3PH</b>	<b>15</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.

<b>GT-DX-150240-03</b>	<b>230-240V/3PH</b>	<b>15</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>GT-DX-150240-03ALT</b>	<b>230-240V/3PH</b>	<b>15</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>GT-DX-150240-03OALT</b>	<b>230-240V/3PH</b>	<b>15</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>GT-DX-150240-04</b>	<b>460-480V/3PH</b>	<b>15</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>GT-DX-150240-04ALT</b>	<b>460-480V/3PH</b>	<b>15</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>GT-DX-150240-04OALT</b>	<b>460-480V/3PH</b>	<b>15</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>GT-DX-150240-05</b>	<b>575-600V/3PH</b>	<b>15</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
<b>GT-DX-150240-05ALT</b>	<b>575-600V/3PH</b>	<b>15</b>	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.

GT-DX-150240-05OALT	575-600V/3PH	15	Heavy duty two stage high efficient cast iron air compressor, duplex configuration. Splash type lubrication. Stainless steel valves. Flywheel designed for excellent pump cooling. Oil sight gauge. Factory set at 120-150 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For commercial, automotive and industrial applications. Factory mounted options available: low oil shutdown for each pump, auto drain (electronic or pneumatic), belt guard aftercoolers.
---------------------	--------------	----	---

## HEAVY DUTY INDUSTRIAL SERIES - SILENT SERIES

MODEL NO.	VOLTAGE	HP	DESCRIPTION
NCSE-20-05-01	230V/1PH	2	Silent series compressor enclosed in soundproof cabinet. Constant air movement by cooling fan(s) over pump. CSA approved. Control panel mounted and wired with hour meter and low oil shutdown (low oil shutdown not available on NCSE-20 and NCSE-30 series). Heavy duty cast iron compressor pump with stainless steel valves, splash type lubrication, flywheel pump cooling. NCSE-20 to NCSE-50: single stage, factory set at 70-90 PSI. NCSE-60 to NCSE-150: two stage, factory set at 120-150 PSI. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For automotive and industrial applications including climate control, laboratories and dental clinics.
NCSE-20-05-02	200-208V/3PH	2	Silent series compressor enclosed in soundproof cabinet. Constant air movement by cooling fan(s) over pump. CSA approved. Control panel mounted and wired with hour meter and low oil shutdown (low oil shutdown not available on NCSE-20 and NCSE-30 series). Heavy duty cast iron compressor pump with stainless steel valves, splash type lubrication, flywheel pump cooling. NCSE-20 to NCSE-50: single stage, factory set at 70-90 PSI. NCSE-60 to NCSE-150: two stage, factory set at 120-150 PSI. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For automotive and industrial applications including climate control, laboratories and dental clinics.
NCSE-20-05-03	230-240V/3PH	2	Silent series compressor enclosed in soundproof cabinet. Constant air movement by cooling fan(s) over pump. CSA approved. Control panel mounted and wired with hour meter and low oil shutdown (low oil shutdown not available on NCSE-20 and NCSE-30 series). Heavy duty cast iron compressor pump with stainless steel valves, splash type lubrication, flywheel pump cooling. NCSE-20 to NCSE-50: single stage, factory set at 70-90 PSI. NCSE-60 to NCSE-150: two stage, factory set at 120-150 PSI. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For automotive and industrial applications including climate control, laboratories and dental clinics.
NCSE-20-05-04	460-480V/3PH	2	Silent series compressor enclosed in soundproof cabinet. Constant air movement by cooling fan(s) over pump. CSA approved. Control panel mounted and wired with hour meter and low oil shutdown (low oil shutdown not available on NCSE-20 and NCSE-30 series). Heavy duty cast iron compressor pump with stainless steel valves, splash type lubrication, flywheel pump cooling. NCSE-20 to NCSE-50: single stage, factory set at 70-90 PSI. NCSE-60 to NCSE-150: two stage, factory set at 120-150 PSI. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For automotive and industrial applications including climate control, laboratories and dental clinics.
NCSE-20-05-05	575-600V/3PH	2	Silent series compressor enclosed in soundproof cabinet. Constant air movement by cooling fan(s) over pump. CSA approved. Control panel mounted and wired with hour meter and low oil shutdown (low oil shutdown not available on NCSE-20 and NCSE-30 series). Heavy duty cast iron compressor pump with stainless steel valves, splash type lubrication, flywheel pump cooling. NCSE-20 to NCSE-50: single stage, factory set at 70-90 PSI. NCSE-60 to NCSE-150: two stage, factory set at 120-150 PSI. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For automotive and industrial applications including climate control, laboratories and dental clinics.
NCSE-20-05-115	115V/1PH	2	Silent series compressor enclosed in soundproof cabinet. Constant air movement by cooling fan(s) over pump. CSA approved. Control panel mounted and wired with hour meter and low oil shutdown (low oil shutdown not available on NCSE-20 and NCSE-30 series). Heavy duty cast iron compressor pump with stainless steel valves, splash type lubrication, flywheel pump cooling. NCSE-20 to NCSE-50: single stage, factory set at 70-90 PSI. NCSE-60 to NCSE-150: two stage, factory set at 120-150 PSI. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For automotive and industrial applications including climate control, laboratories and dental clinics.

<b>NCSE-20-075-01</b>	<b>230V/1PH</b>	<b>4</b>	Silent series compressor enclosed in soundproof cabinet. Constant air movement by cooling fan(s) over pump. CSA approved. Control panel mounted and wired with hour meter and low oil shutdown (low oil shutdown not available on NCSE-20 and NCSE-30 series). Heavy duty cast iron compressor pump with stainless steel valves, splash type lubrication, flywheel pump cooling. NCSE-20 to NCSE-50: single stage, factory set at 70-90 PSI. NCSE-60 to NCSE-150: two stage, factory set at 120-150 PSI. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For automotive and industrial applications including climate control, laboratories and dental clinics.
<b>NCSE-20-075-02</b>	<b>200-208V/3PH</b>	<b>4</b>	Silent series compressor enclosed in soundproof cabinet. Constant air movement by cooling fan(s) over pump. CSA approved. Control panel mounted and wired with hour meter and low oil shutdown (low oil shutdown not available on NCSE-20 and NCSE-30 series). Heavy duty cast iron compressor pump with stainless steel valves, splash type lubrication, flywheel pump cooling. NCSE-20 to NCSE-50: single stage, factory set at 70-90 PSI. NCSE-60 to NCSE-150: two stage, factory set at 120-150 PSI. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For automotive and industrial applications including climate control, laboratories and dental clinics.
<b>NCSE-20-075-03</b>	<b>230-240V/3PH</b>	<b>4</b>	Silent series compressor enclosed in soundproof cabinet. Constant air movement by cooling fan(s) over pump. CSA approved. Control panel mounted and wired with hour meter and low oil shutdown (low oil shutdown not available on NCSE-20 and NCSE-30 series). Heavy duty cast iron compressor pump with stainless steel valves, splash type lubrication, flywheel pump cooling. NCSE-20 to NCSE-50: single stage, factory set at 70-90 PSI. NCSE-60 to NCSE-150: two stage, factory set at 120-150 PSI. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For automotive and industrial applications including climate control, laboratories and dental clinics.
<b>NCSE-20-075-04</b>	<b>460-480V/3PH</b>	<b>4</b>	Silent series compressor enclosed in soundproof cabinet. Constant air movement by cooling fan(s) over pump. CSA approved. Control panel mounted and wired with hour meter and low oil shutdown (low oil shutdown not available on NCSE-20 and NCSE-30 series). Heavy duty cast iron compressor pump with stainless steel valves, splash type lubrication, flywheel pump cooling. NCSE-20 to NCSE-50: single stage, factory set at 70-90 PSI. NCSE-60 to NCSE-150: two stage, factory set at 120-150 PSI. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For automotive and industrial applications including climate control, laboratories and dental clinics.
<b>NCSE-20-075-05</b>	<b>575-600V/3PH</b>	<b>4</b>	Silent series compressor enclosed in soundproof cabinet. Constant air movement by cooling fan(s) over pump. CSA approved. Control panel mounted and wired with hour meter and low oil shutdown (low oil shutdown not available on NCSE-20 and NCSE-30 series). Heavy duty cast iron compressor pump with stainless steel valves, splash type lubrication, flywheel pump cooling. NCSE-20 to NCSE-50: single stage, factory set at 70-90 PSI. NCSE-60 to NCSE-150: two stage, factory set at 120-150 PSI. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For automotive and industrial applications including climate control, laboratories and dental clinics.
<b>NCSE-20-075-115</b>	<b>115V/1PH</b>	<b>4</b>	Silent series compressor enclosed in soundproof cabinet. Constant air movement by cooling fan(s) over pump. CSA approved. Control panel mounted and wired with hour meter and low oil shutdown (low oil shutdown not available on NCSE-20 and NCSE-30 series). Heavy duty cast iron compressor pump with stainless steel valves, splash type lubrication, flywheel pump cooling. NCSE-20 to NCSE-50: single stage, factory set at 70-90 PSI. NCSE-60 to NCSE-150: two stage, factory set at 120-150 PSI. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For automotive and industrial applications including climate control, laboratories and dental clinics.
<b>NCSE-30-01-01</b>	<b>230V/1PH</b>	<b>1</b>	Silent series compressor enclosed in soundproof cabinet. Constant air movement by cooling fan(s) over pump. CSA approved. Control panel mounted and wired with hour meter and low oil shutdown (low oil shutdown not available on NCSE-20 and NCSE-30 series). Heavy duty cast iron compressor pump with stainless steel valves, splash type lubrication, flywheel pump cooling. NCSE-20 to NCSE-50: single stage, factory set at 70-90 PSI. NCSE-60 to NCSE-150: two stage, factory set at 120-150 PSI. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For automotive and industrial applications including climate control, laboratories and dental clinics.
<b>NCSE-30-01-02</b>	<b>200-208V/3PH</b>	<b>1</b>	Silent series compressor enclosed in soundproof cabinet. Constant air movement by cooling fan(s) over pump. CSA approved. Control panel mounted and wired with hour meter and low oil shutdown (low oil shutdown not available on NCSE-20 and NCSE-30 series). Heavy duty cast iron compressor pump with stainless steel valves, splash type lubrication, flywheel pump cooling. NCSE-20 to NCSE-50: single stage, factory set at 70-90 PSI. NCSE-60 to NCSE-150: two stage, factory set at 120-150 PSI. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For automotive and industrial applications including climate control, laboratories and dental clinics.

<b>NCSE-30-01-03</b>	<b>230-240V/3PH</b>	<b>1</b>	Silent series compressor enclosed in soundproof cabinet. Constant air movement by cooling fan(s) over pump. CSA approved. Control panel mounted and wired with hour meter and low oil shutdown (low oil shutdown not available on NCSE-20 and NCSE-30 series). Heavy duty cast iron compressor pump with stainless steel valves, splash type lubrication, flywheel pump cooling. NCSE-20 to NCSE-50: single stage, factory set at 70-90 PSI. NCSE-60 to NCSE-150: two stage, factory set at 120-150 PSI. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For automotive and industrial applications including climate control, laboratories and dental clinics.
<b>NCSE-30-01-04</b>	<b>460-480V/3PH</b>	<b>1</b>	Silent series compressor enclosed in soundproof cabinet. Constant air movement by cooling fan(s) over pump. CSA approved. Control panel mounted and wired with hour meter and low oil shutdown (low oil shutdown not available on NCSE-20 and NCSE-30 series). Heavy duty cast iron compressor pump with stainless steel valves, splash type lubrication, flywheel pump cooling. NCSE-20 to NCSE-50: single stage, factory set at 70-90 PSI. NCSE-60 to NCSE-150: two stage, factory set at 120-150 PSI. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For automotive and industrial applications including climate control, laboratories and dental clinics.
<b>NCSE-30-01-05</b>	<b>575-600V/3PH</b>	<b>1</b>	Silent series compressor enclosed in soundproof cabinet. Constant air movement by cooling fan(s) over pump. CSA approved. Control panel mounted and wired with hour meter and low oil shutdown (low oil shutdown not available on NCSE-20 and NCSE-30 series). Heavy duty cast iron compressor pump with stainless steel valves, splash type lubrication, flywheel pump cooling. NCSE-20 to NCSE-50: single stage, factory set at 70-90 PSI. NCSE-60 to NCSE-150: two stage, factory set at 120-150 PSI. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For automotive and industrial applications including climate control, laboratories and dental clinics.
<b>NCSE-30-01-115</b>	<b>115V/1PH</b>	<b>1</b>	Silent series compressor enclosed in soundproof cabinet. Constant air movement by cooling fan(s) over pump. CSA approved. Control panel mounted and wired with hour meter and low oil shutdown (low oil shutdown not available on NCSE-20 and NCSE-30 series). Heavy duty cast iron compressor pump with stainless steel valves, splash type lubrication, flywheel pump cooling. NCSE-20 to NCSE-50: single stage, factory set at 70-90 PSI. NCSE-60 to NCSE-150: two stage, factory set at 120-150 PSI. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For automotive and industrial applications including climate control, laboratories and dental clinics.
<b>NCSE-50-015-01</b>	<b>230V/1PH</b>	<b>2</b>	Silent series compressor enclosed in soundproof cabinet. Constant air movement by cooling fan(s) over pump. CSA approved. Control panel mounted and wired with hour meter and low oil shutdown (low oil shutdown not available on NCSE-20 and NCSE-30 series). Heavy duty cast iron compressor pump with stainless steel valves, splash type lubrication, flywheel pump cooling. NCSE-20 to NCSE-50: single stage, factory set at 70-90 PSI. NCSE-60 to NCSE-150: two stage, factory set at 120-150 PSI. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For automotive and industrial applications including climate control, laboratories and dental clinics.
<b>NCSE-50-015-02</b>	<b>200-208V/3PH</b>	<b>2</b>	Silent series compressor enclosed in soundproof cabinet. Constant air movement by cooling fan(s) over pump. CSA approved. Control panel mounted and wired with hour meter and low oil shutdown (low oil shutdown not available on NCSE-20 and NCSE-30 series). Heavy duty cast iron compressor pump with stainless steel valves, splash type lubrication, flywheel pump cooling. NCSE-20 to NCSE-50: single stage, factory set at 70-90 PSI. NCSE-60 to NCSE-150: two stage, factory set at 120-150 PSI. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For automotive and industrial applications including climate control, laboratories and dental clinics.
<b>NCSE-50-015-03</b>	<b>230-240V/3PH</b>	<b>2</b>	Silent series compressor enclosed in soundproof cabinet. Constant air movement by cooling fan(s) over pump. CSA approved. Control panel mounted and wired with hour meter and low oil shutdown (low oil shutdown not available on NCSE-20 and NCSE-30 series). Heavy duty cast iron compressor pump with stainless steel valves, splash type lubrication, flywheel pump cooling. NCSE-20 to NCSE-50: single stage, factory set at 70-90 PSI. NCSE-60 to NCSE-150: two stage, factory set at 120-150 PSI. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For automotive and industrial applications including climate control, laboratories and dental clinics.
<b>NCSE-50-015-04</b>	<b>460-480V/3PH</b>	<b>2</b>	Silent series compressor enclosed in soundproof cabinet. Constant air movement by cooling fan(s) over pump. CSA approved. Control panel mounted and wired with hour meter and low oil shutdown (low oil shutdown not available on NCSE-20 and NCSE-30 series). Heavy duty cast iron compressor pump with stainless steel valves, splash type lubrication, flywheel pump cooling. NCSE-20 to NCSE-50: single stage, factory set at 70-90 PSI. NCSE-60 to NCSE-150: two stage, factory set at 120-150 PSI. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For automotive and industrial applications including climate control, laboratories and dental clinics.

<b>NCSE-50-015-05</b>	<b>575-600V/3PH</b>	<b>2</b>	Silent series compressor enclosed in soundproof cabinet. Constant air movement by cooling fan(s) over pump. CSA approved. Control panel mounted and wired with hour meter and low oil shutdown (low oil shutdown not available on NCSE-20 and NCSE-30 series). Heavy duty cast iron compressor pump with stainless steel valves, splash type lubrication, flywheel pump cooling. NCSE-20 to NCSE-50: single stage, factory set at 70-90 PSI. NCSE-60 to NCSE-150: two stage, factory set at 120-150 PSI. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For automotive and industrial applications including climate control, laboratories and dental clinics.
<b>NCSE-50-015-115</b>	<b>115V/1PH</b>	<b>2</b>	Silent series compressor enclosed in soundproof cabinet. Constant air movement by cooling fan(s) over pump. CSA approved. Control panel mounted and wired with hour meter and low oil shutdown (low oil shutdown not available on NCSE-20 and NCSE-30 series). Heavy duty cast iron compressor pump with stainless steel valves, splash type lubrication, flywheel pump cooling. NCSE-20 to NCSE-50: single stage, factory set at 70-90 PSI. NCSE-60 to NCSE-150: two stage, factory set at 120-150 PSI. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For automotive and industrial applications including climate control, laboratories and dental clinics.
<b>NCSE-50-02-01</b>	<b>230V/1PH</b>	<b>2</b>	Silent series compressor enclosed in soundproof cabinet. Constant air movement by cooling fan(s) over pump. CSA approved. Control panel mounted and wired with hour meter and low oil shutdown (low oil shutdown not available on NCSE-20 and NCSE-30 series). Heavy duty cast iron compressor pump with stainless steel valves, splash type lubrication, flywheel pump cooling. NCSE-20 to NCSE-50: single stage, factory set at 70-90 PSI. NCSE-60 to NCSE-150: two stage, factory set at 120-150 PSI. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For automotive and industrial applications including climate control, laboratories and dental clinics.
<b>NCSE-50-02-02</b>	<b>200-208V/3PH</b>	<b>2</b>	Silent series compressor enclosed in soundproof cabinet. Constant air movement by cooling fan(s) over pump. CSA approved. Control panel mounted and wired with hour meter and low oil shutdown (low oil shutdown not available on NCSE-20 and NCSE-30 series). Heavy duty cast iron compressor pump with stainless steel valves, splash type lubrication, flywheel pump cooling. NCSE-20 to NCSE-50: single stage, factory set at 70-90 PSI. NCSE-60 to NCSE-150: two stage, factory set at 120-150 PSI. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For automotive and industrial applications including climate control, laboratories and dental clinics.
<b>NCSE-50-02-03</b>	<b>230-240V/3PH</b>	<b>2</b>	Silent series compressor enclosed in soundproof cabinet. Constant air movement by cooling fan(s) over pump. CSA approved. Control panel mounted and wired with hour meter and low oil shutdown (low oil shutdown not available on NCSE-20 and NCSE-30 series). Heavy duty cast iron compressor pump with stainless steel valves, splash type lubrication, flywheel pump cooling. NCSE-20 to NCSE-50: single stage, factory set at 70-90 PSI. NCSE-60 to NCSE-150: two stage, factory set at 120-150 PSI. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For automotive and industrial applications including climate control, laboratories and dental clinics.
<b>NCSE-50-02-04</b>	<b>460-480V/3PH</b>	<b>2</b>	Silent series compressor enclosed in soundproof cabinet. Constant air movement by cooling fan(s) over pump. CSA approved. Control panel mounted and wired with hour meter and low oil shutdown (low oil shutdown not available on NCSE-20 and NCSE-30 series). Heavy duty cast iron compressor pump with stainless steel valves, splash type lubrication, flywheel pump cooling. NCSE-20 to NCSE-50: single stage, factory set at 70-90 PSI. NCSE-60 to NCSE-150: two stage, factory set at 120-150 PSI. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For automotive and industrial applications including climate control, laboratories and dental clinics.
<b>NCSE-50-02-05</b>	<b>575-600V/3PH</b>	<b>2</b>	Silent series compressor enclosed in soundproof cabinet. Constant air movement by cooling fan(s) over pump. CSA approved. Control panel mounted and wired with hour meter and low oil shutdown (low oil shutdown not available on NCSE-20 and NCSE-30 series). Heavy duty cast iron compressor pump with stainless steel valves, splash type lubrication, flywheel pump cooling. NCSE-20 to NCSE-50: single stage, factory set at 70-90 PSI. NCSE-60 to NCSE-150: two stage, factory set at 120-150 PSI. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For automotive and industrial applications including climate control, laboratories and dental clinics.
<b>NCSE-50-02-115</b>	<b>115V/1PH</b>	<b>2</b>	Silent series compressor enclosed in soundproof cabinet. Constant air movement by cooling fan(s) over pump. CSA approved. Control panel mounted and wired with hour meter and low oil shutdown (low oil shutdown not available on NCSE-20 and NCSE-30 series). Heavy duty cast iron compressor pump with stainless steel valves, splash type lubrication, flywheel pump cooling. NCSE-20 to NCSE-50: single stage, factory set at 70-90 PSI. NCSE-60 to NCSE-150: two stage, factory set at 120-150 PSI. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For automotive and industrial applications including climate control, laboratories and dental clinics.

<b>NCSE-60-03-01</b>	<b>230V/1PH</b>	<b>3</b>	Silent series compressor enclosed in soundproof cabinet. Constant air movement by cooling fan(s) over pump. CSA approved. Control panel mounted and wired with hour meter and low oil shutdown (low oil shutdown not available on NCSE-20 and NCSE-30 series). Heavy duty cast iron compressor pump with stainless steel valves, splash type lubrication, flywheel pump cooling. NCSE-20 to NCSE-50: single stage, factory set at 70-90 PSI. NCSE-60 to NCSE-150: two stage, factory set at 120-150 PSI. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For automotive and industrial applications including climate control, laboratories and dental clinics.
<b>NCSE-60-03-02</b>	<b>200-208V/3PH</b>	<b>3</b>	Silent series compressor enclosed in soundproof cabinet. Constant air movement by cooling fan(s) over pump. CSA approved. Control panel mounted and wired with hour meter and low oil shutdown (low oil shutdown not available on NCSE-20 and NCSE-30 series). Heavy duty cast iron compressor pump with stainless steel valves, splash type lubrication, flywheel pump cooling. NCSE-20 to NCSE-50: single stage, factory set at 70-90 PSI. NCSE-60 to NCSE-150: two stage, factory set at 120-150 PSI. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For automotive and industrial applications including climate control, laboratories and dental clinics.
<b>NCSE-60-03-03</b>	<b>230-240V/3PH</b>	<b>3</b>	Silent series compressor enclosed in soundproof cabinet. Constant air movement by cooling fan(s) over pump. CSA approved. Control panel mounted and wired with hour meter and low oil shutdown (low oil shutdown not available on NCSE-20 and NCSE-30 series). Heavy duty cast iron compressor pump with stainless steel valves, splash type lubrication, flywheel pump cooling. NCSE-20 to NCSE-50: single stage, factory set at 70-90 PSI. NCSE-60 to NCSE-150: two stage, factory set at 120-150 PSI. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For automotive and industrial applications including climate control, laboratories and dental clinics.
<b>NCSE-60-03-04</b>	<b>460-480V/3PH</b>	<b>3</b>	Silent series compressor enclosed in soundproof cabinet. Constant air movement by cooling fan(s) over pump. CSA approved. Control panel mounted and wired with hour meter and low oil shutdown (low oil shutdown not available on NCSE-20 and NCSE-30 series). Heavy duty cast iron compressor pump with stainless steel valves, splash type lubrication, flywheel pump cooling. NCSE-20 to NCSE-50: single stage, factory set at 70-90 PSI. NCSE-60 to NCSE-150: two stage, factory set at 120-150 PSI. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For automotive and industrial applications including climate control, laboratories and dental clinics.
<b>NCSE-60-03-05</b>	<b>575-600V/3PH</b>	<b>3</b>	Silent series compressor enclosed in soundproof cabinet. Constant air movement by cooling fan(s) over pump. CSA approved. Control panel mounted and wired with hour meter and low oil shutdown (low oil shutdown not available on NCSE-20 and NCSE-30 series). Heavy duty cast iron compressor pump with stainless steel valves, splash type lubrication, flywheel pump cooling. NCSE-20 to NCSE-50: single stage, factory set at 70-90 PSI. NCSE-60 to NCSE-150: two stage, factory set at 120-150 PSI. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For automotive and industrial applications including climate control, laboratories and dental clinics.
<b>NCSE-60-03-115</b>	<b>115V/1PH</b>	<b>3</b>	Silent series compressor enclosed in soundproof cabinet. Constant air movement by cooling fan(s) over pump. CSA approved. Control panel mounted and wired with hour meter and low oil shutdown (low oil shutdown not available on NCSE-20 and NCSE-30 series). Heavy duty cast iron compressor pump with stainless steel valves, splash type lubrication, flywheel pump cooling. NCSE-20 to NCSE-50: single stage, factory set at 70-90 PSI. NCSE-60 to NCSE-150: two stage, factory set at 120-150 PSI. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For automotive and industrial applications including climate control, laboratories and dental clinics.
<b>NCSE-75-50-01</b>	<b>230V/1PH</b>	<b>5</b>	Silent series compressor enclosed in soundproof cabinet. Constant air movement by cooling fan(s) over pump. CSA approved. Control panel mounted and wired with hour meter and low oil shutdown (low oil shutdown not available on NCSE-20 and NCSE-30 series). Heavy duty cast iron compressor pump with stainless steel valves, splash type lubrication, flywheel pump cooling. NCSE-20 to NCSE-50: single stage, factory set at 70-90 PSI. NCSE-60 to NCSE-150: two stage, factory set at 120-150 PSI. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For automotive and industrial applications including climate control, laboratories and dental clinics.
<b>NCSE-75-50-02</b>	<b>200-208V/3PH</b>	<b>5</b>	Silent series compressor enclosed in soundproof cabinet. Constant air movement by cooling fan(s) over pump. CSA approved. Control panel mounted and wired with hour meter and low oil shutdown (low oil shutdown not available on NCSE-20 and NCSE-30 series). Heavy duty cast iron compressor pump with stainless steel valves, splash type lubrication, flywheel pump cooling. NCSE-20 to NCSE-50: single stage, factory set at 70-90 PSI. NCSE-60 to NCSE-150: two stage, factory set at 120-150 PSI. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For automotive and industrial applications including climate control, laboratories and dental clinics.

<b>NCSE-75-50-03</b>	<b>230-240V/3PH</b>	<b>5</b>	Silent series compressor enclosed in soundproof cabinet. Constant air movement by cooling fan(s) over pump. CSA approved. Control panel mounted and wired with hour meter and low oil shutdown (low oil shutdown not available on NCSE-20 and NCSE-30 series). Heavy duty cast iron compressor pump with stainless steel valves, splash type lubrication, flywheel pump cooling. NCSE-20 to NCSE-50: single stage, factory set at 70-90 PSI. NCSE-60 to NCSE-150: two stage, factory set at 120-150 PSI. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For automotive and industrial applications including climate control, laboratories and dental clinics.
<b>NCSE-75-50-04</b>	<b>460-480V/3PH</b>	<b>5</b>	Silent series compressor enclosed in soundproof cabinet. Constant air movement by cooling fan(s) over pump. CSA approved. Control panel mounted and wired with hour meter and low oil shutdown (low oil shutdown not available on NCSE-20 and NCSE-30 series). Heavy duty cast iron compressor pump with stainless steel valves, splash type lubrication, flywheel pump cooling. NCSE-20 to NCSE-50: single stage, factory set at 70-90 PSI. NCSE-60 to NCSE-150: two stage, factory set at 120-150 PSI. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For automotive and industrial applications including climate control, laboratories and dental clinics.
<b>NCSE-75-50-05</b>	<b>575-600V/3PH</b>	<b>5</b>	Silent series compressor enclosed in soundproof cabinet. Constant air movement by cooling fan(s) over pump. CSA approved. Control panel mounted and wired with hour meter and low oil shutdown (low oil shutdown not available on NCSE-20 and NCSE-30 series). Heavy duty cast iron compressor pump with stainless steel valves, splash type lubrication, flywheel pump cooling. NCSE-20 to NCSE-50: single stage, factory set at 70-90 PSI. NCSE-60 to NCSE-150: two stage, factory set at 120-150 PSI. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For automotive and industrial applications including climate control, laboratories and dental clinics.
<b>NCSE-100-75-01</b>	<b>230V/1PH</b>	<b>7.5</b>	Silent series compressor enclosed in soundproof cabinet. Constant air movement by cooling fan(s) over pump. CSA approved. Control panel mounted and wired with hour meter and low oil shutdown (low oil shutdown not available on NCSE-20 and NCSE-30 series). Heavy duty cast iron compressor pump with stainless steel valves, splash type lubrication, flywheel pump cooling. NCSE-20 to NCSE-50: single stage, factory set at 70-90 PSI. NCSE-60 to NCSE-150: two stage, factory set at 120-150 PSI. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For automotive and industrial applications including climate control, laboratories and dental clinics.
<b>NCSE-100-75-02</b>	<b>200-208V/3PH</b>	<b>7.5</b>	Silent series compressor enclosed in soundproof cabinet. Constant air movement by cooling fan(s) over pump. CSA approved. Control panel mounted and wired with hour meter and low oil shutdown (low oil shutdown not available on NCSE-20 and NCSE-30 series). Heavy duty cast iron compressor pump with stainless steel valves, splash type lubrication, flywheel pump cooling. NCSE-20 to NCSE-50: single stage, factory set at 70-90 PSI. NCSE-60 to NCSE-150: two stage, factory set at 120-150 PSI. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For automotive and industrial applications including climate control, laboratories and dental clinics.
<b>NCSE-100-75-03</b>	<b>230-240V/3PH</b>	<b>7.5</b>	Silent series compressor enclosed in soundproof cabinet. Constant air movement by cooling fan(s) over pump. CSA approved. Control panel mounted and wired with hour meter and low oil shutdown (low oil shutdown not available on NCSE-20 and NCSE-30 series). Heavy duty cast iron compressor pump with stainless steel valves, splash type lubrication, flywheel pump cooling. NCSE-20 to NCSE-50: single stage, factory set at 70-90 PSI. NCSE-60 to NCSE-150: two stage, factory set at 120-150 PSI. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For automotive and industrial applications including climate control, laboratories and dental clinics.
<b>NCSE-100-75-04</b>	<b>460-480V/3PH</b>	<b>7.5</b>	Silent series compressor enclosed in soundproof cabinet. Constant air movement by cooling fan(s) over pump. CSA approved. Control panel mounted and wired with hour meter and low oil shutdown (low oil shutdown not available on NCSE-20 and NCSE-30 series). Heavy duty cast iron compressor pump with stainless steel valves, splash type lubrication, flywheel pump cooling. NCSE-20 to NCSE-50: single stage, factory set at 70-90 PSI. NCSE-60 to NCSE-150: two stage, factory set at 120-150 PSI. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For automotive and industrial applications including climate control, laboratories and dental clinics.
<b>NCSE-100-75-05</b>	<b>575-600V/3PH</b>	<b>7.5</b>	Silent series compressor enclosed in soundproof cabinet. Constant air movement by cooling fan(s) over pump. CSA approved. Control panel mounted and wired with hour meter and low oil shutdown (low oil shutdown not available on NCSE-20 and NCSE-30 series). Heavy duty cast iron compressor pump with stainless steel valves, splash type lubrication, flywheel pump cooling. NCSE-20 to NCSE-50: single stage, factory set at 70-90 PSI. NCSE-60 to NCSE-150: two stage, factory set at 120-150 PSI. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For automotive and industrial applications including climate control, laboratories and dental clinics.

<b>NCSE-100-10-01</b>	<b>230V/1PH</b>	<b>10</b>	Silent series compressor enclosed in soundproof cabinet. Constant air movement by cooling fan(s) over pump. CSA approved. Control panel mounted and wired with hour meter and low oil shutdown (low oil shutdown not available on NCSE-20 and NCSE-30 series). Heavy duty cast iron compressor pump with stainless steel valves, splash type lubrication, flywheel pump cooling. NCSE-20 to NCSE-50: single stage, factory set at 70-90 PSI. NCSE-60 to NCSE-150: two stage, factory set at 120-150 PSI. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For automotive and industrial applications including climate control, laboratories and dental clinics.
<b>NCSE-100-10-02</b>	<b>200-208V/3PH</b>	<b>10</b>	Silent series compressor enclosed in soundproof cabinet. Constant air movement by cooling fan(s) over pump. CSA approved. Control panel mounted and wired with hour meter and low oil shutdown (low oil shutdown not available on NCSE-20 and NCSE-30 series). Heavy duty cast iron compressor pump with stainless steel valves, splash type lubrication, flywheel pump cooling. NCSE-20 to NCSE-50: single stage, factory set at 70-90 PSI. NCSE-60 to NCSE-150: two stage, factory set at 120-150 PSI. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For automotive and industrial applications including climate control, laboratories and dental clinics.
<b>NCSE-100-10-03</b>	<b>230-240V/3PH</b>	<b>10</b>	Silent series compressor enclosed in soundproof cabinet. Constant air movement by cooling fan(s) over pump. CSA approved. Control panel mounted and wired with hour meter and low oil shutdown (low oil shutdown not available on NCSE-20 and NCSE-30 series). Heavy duty cast iron compressor pump with stainless steel valves, splash type lubrication, flywheel pump cooling. NCSE-20 to NCSE-50: single stage, factory set at 70-90 PSI. NCSE-60 to NCSE-150: two stage, factory set at 120-150 PSI. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For automotive and industrial applications including climate control, laboratories and dental clinics.
<b>NCSE-100-10-04</b>	<b>460-480V/3PH</b>	<b>10</b>	Silent series compressor enclosed in soundproof cabinet. Constant air movement by cooling fan(s) over pump. CSA approved. Control panel mounted and wired with hour meter and low oil shutdown (low oil shutdown not available on NCSE-20 and NCSE-30 series). Heavy duty cast iron compressor pump with stainless steel valves, splash type lubrication, flywheel pump cooling. NCSE-20 to NCSE-50: single stage, factory set at 70-90 PSI. NCSE-60 to NCSE-150: two stage, factory set at 120-150 PSI. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For automotive and industrial applications including climate control, laboratories and dental clinics.
<b>NCSE-100-10-05</b>	<b>575-600V/3PH</b>	<b>10</b>	Silent series compressor enclosed in soundproof cabinet. Constant air movement by cooling fan(s) over pump. CSA approved. Control panel mounted and wired with hour meter and low oil shutdown (low oil shutdown not available on NCSE-20 and NCSE-30 series). Heavy duty cast iron compressor pump with stainless steel valves, splash type lubrication, flywheel pump cooling. NCSE-20 to NCSE-50: single stage, factory set at 70-90 PSI. NCSE-60 to NCSE-150: two stage, factory set at 120-150 PSI. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For automotive and industrial applications including climate control, laboratories and dental clinics.
<b>NCSE-150-15-02</b>	<b>200-208V/3PH</b>	<b>15</b>	Silent series compressor enclosed in soundproof cabinet. Constant air movement by cooling fan(s) over pump. CSA approved. Control panel mounted and wired with hour meter and low oil shutdown (low oil shutdown not available on NCSE-20 and NCSE-30 series). Heavy duty cast iron compressor pump with stainless steel valves, splash type lubrication, flywheel pump cooling. NCSE-20 to NCSE-50: single stage, factory set at 70-90 PSI. NCSE-60 to NCSE-150: two stage, factory set at 120-150 PSI. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For automotive and industrial applications including climate control, laboratories and dental clinics.
<b>NCSE-150-15-03</b>	<b>230-240V/3PH</b>	<b>15</b>	Silent series compressor enclosed in soundproof cabinet. Constant air movement by cooling fan(s) over pump. CSA approved. Control panel mounted and wired with hour meter and low oil shutdown (low oil shutdown not available on NCSE-20 and NCSE-30 series). Heavy duty cast iron compressor pump with stainless steel valves, splash type lubrication, flywheel pump cooling. NCSE-20 to NCSE-50: single stage, factory set at 70-90 PSI. NCSE-60 to NCSE-150: two stage, factory set at 120-150 PSI. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For automotive and industrial applications including climate control, laboratories and dental clinics.
<b>NCSE-150-15-04</b>	<b>460-480V/3PH</b>	<b>15</b>	Silent series compressor enclosed in soundproof cabinet. Constant air movement by cooling fan(s) over pump. CSA approved. Control panel mounted and wired with hour meter and low oil shutdown (low oil shutdown not available on NCSE-20 and NCSE-30 series). Heavy duty cast iron compressor pump with stainless steel valves, splash type lubrication, flywheel pump cooling. NCSE-20 to NCSE-50: single stage, factory set at 70-90 PSI. NCSE-60 to NCSE-150: two stage, factory set at 120-150 PSI. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For automotive and industrial applications including climate control, laboratories and dental clinics.

<b>NCSE-150-15-05</b>	<b>575-600V/3PH</b>	<b>15</b>	Silent series compressor enclosed in soundproof cabinet. Constant air movement by cooling fan(s) over pump. CSA approved. Control panel mounted and wired with hour meter and low oil shutdown (low oil shutdown not available on NCSE-20 and NCSE-30 series). Heavy duty cast iron compressor pump with stainless steel valves, splash type lubrication, flywheel pump cooling. NCSE-20 to NCSE-50: single stage, factory set at 70-90 PSI. NCSE-60 to NCSE-150: two stage, factory set at 120-150 PSI. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For automotive and industrial applications including climate control, laboratories and dental clinics.
-----------------------	---------------------	-----------	--

## HEAVY DUTY INDUSTRIAL SERIES - GAS ENGINE TANK MOUNTED

MODEL NO.	VOLTAGE	HP	DESCRIPTION
<b>PUK-5530G</b>	<b>N/A (Gas)</b>	<b>5.5</b>	Heavy duty single and two stage high efficient cast iron air compressor with Honda gas engine, low oil alert. Electric start standard on 11HP, 13HP and 20HP engines. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Head unloaders. Single stage: factory set at 90-125 PSI. Two stage: factory set at 140-175 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>PUK-9030G</b>	<b>N/A (Gas)</b>	<b>9</b>	Heavy duty single and two stage high efficient cast iron air compressor with Honda gas engine, low oil alert. Electric start standard on 11HP, 13HP and 20HP engines. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Head unloaders. Single stage: factory set at 90-125 PSI. Two stage: factory set at 140-175 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>TUK-1130GE</b>	<b>N/A (Gas)</b>	<b>11</b>	Heavy duty single and two stage high efficient cast iron air compressor with Honda gas engine, low oil alert. Electric start standard on 11HP, 13HP and 20HP engines. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Head unloaders. Single stage: factory set at 90-125 PSI. Two stage: factory set at 140-175 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>TUK-1130GEC</b>	<b>N/A (Gas)</b>	<b>11</b>	Heavy duty single and two stage high efficient cast iron air compressor with Honda gas engine, low oil alert. Electric start standard on 11HP, 13HP and 20HP engines. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Head unloaders. Single stage: factory set at 90-125 PSI. Two stage: factory set at 140-175 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>TUE-1330GE</b>		<b>13</b>	Heavy duty single and two stage high efficient cast iron air compressor with Honda gas engine, low oil alert. Electric start standard on 11HP, 13HP and 20HP engines. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Head unloaders. Single stage: factory set at 90-125 PSI. Two stage: factory set at 140-175 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>TUE-1330GEC</b>		<b>13</b>	Heavy duty single and two stage high efficient cast iron air compressor with Honda gas engine, low oil alert. Electric start standard on 11HP, 13HP and 20HP engines. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Head unloaders. Single stage: factory set at 90-125 PSI. Two stage: factory set at 140-175 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty.

<b>TUK-1330GE</b>	<b>N/A (Gas)</b>	<b>13</b>	Heavy duty single and two stage high efficient cast iron air compressor with Honda gas engine, low oil alert. Electric start standard on 11HP, 13HP and 20HP engines. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Head unloaders. Single stage: factory set at 90-125 PSI. Two stage: factory set at 140-175 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>TUK-1330GEC</b>	<b>N/A (Gas)</b>	<b>13</b>	Heavy duty single and two stage high efficient cast iron air compressor with Honda gas engine, low oil alert. Electric start standard on 11HP, 13HP and 20HP engines. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Head unloaders. Single stage: factory set at 90-125 PSI. Two stage: factory set at 140-175 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>TUK-2030GEC</b>	<b>N/A (Gas)</b>	<b>20</b>	Heavy duty single and two stage high efficient cast iron air compressor with Honda gas engine, low oil alert. Electric start standard on 11HP, 13HP and 20HP engines. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Head unloaders. Single stage: factory set at 90-125 PSI. Two stage: factory set at 140-175 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty.

## HEAVY DUTY INDUSTRIAL SERIES - GAS ENGINE BASE MOUNTED

MODEL NO.	VOLTAGE	HP	DESCRIPTION
<b>PUK-5500G</b>	<b>N/A (Gas)</b>	<b>5.5</b>	Heavy duty single and two stage high efficient cast iron air compressor with Honda gas engine, low oil alert. Electric start standard on 11HP, 13HP and 20HP engines. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Head unloaders. Single stage: factory set at 90-125 PSI. Two stage: factory set at 140-175 PSI. Equipped with liquid filled gauge, snubber and flex hose. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>PUK-9000G</b>	<b>N/A (Gas)</b>	<b>9</b>	Heavy duty single and two stage high efficient cast iron air compressor with Honda gas engine, low oil alert. Electric start standard on 11HP, 13HP and 20HP engines. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Head unloaders. Single stage: factory set at 90-125 PSI. Two stage: factory set at 140-175 PSI. Equipped with liquid filled gauge, snubber and flex hose. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>TUK-1100GE</b>	<b>N/A (Gas)</b>	<b>11</b>	Heavy duty single and two stage high efficient cast iron air compressor with Honda gas engine, low oil alert. Electric start standard on 11HP, 13HP and 20HP engines. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Head unloaders. Single stage: factory set at 90-125 PSI. Two stage: factory set at 140-175 PSI. Equipped with liquid filled gauge, snubber and flex hose. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>TUK-1100GEC</b>	<b>N/A (Gas)</b>	<b>11</b>	Heavy duty single and two stage high efficient cast iron air compressor with Honda gas engine, low oil alert. Electric start standard on 11HP, 13HP and 20HP engines. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Head unloaders. Single stage: factory set at 90-125 PSI. Two stage: factory set at 140-175 PSI. Equipped with liquid filled gauge, snubber and flex hose. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty.

<b>TUE-1300GE</b>		<b>13</b>	Heavy duty single and two stage high efficient cast iron air compressor with Honda gas engine, low oil alert. Electric start standard on 11HP, 13HP and 20HP engines. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Head unloaders. Single stage: factory set at 90-125 PSI. Two stage: factory set at 140-175 PSI. Equipped with liquid filled gauge, snubber and flex hose. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>TUE-1300GEC</b>		<b>13</b>	Heavy duty single and two stage high efficient cast iron air compressor with Honda gas engine, low oil alert. Electric start standard on 11HP, 13HP and 20HP engines. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Head unloaders. Single stage: factory set at 90-125 PSI. Two stage: factory set at 140-175 PSI. Equipped with liquid filled gauge, snubber and flex hose. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>TUK-1300GE</b>	<b>N/A (Gas)</b>	<b>13</b>	Heavy duty single and two stage high efficient cast iron air compressor with Honda gas engine, low oil alert. Electric start standard on 11HP, 13HP and 20HP engines. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Head unloaders. Single stage: factory set at 90-125 PSI. Two stage: factory set at 140-175 PSI. Equipped with liquid filled gauge, snubber and flex hose. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>TUK-1300GEC</b>	<b>N/A (Gas)</b>	<b>13</b>	Heavy duty single and two stage high efficient cast iron air compressor with Honda gas engine, low oil alert. Electric start standard on 11HP, 13HP and 20HP engines. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Head unloaders. Single stage: factory set at 90-125 PSI. Two stage: factory set at 140-175 PSI. Equipped with liquid filled gauge, snubber and flex hose. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>TUK-2000GEC</b>	<b>N/A (Gas)</b>	<b>20</b>	Heavy duty single and two stage high efficient cast iron air compressor with Honda gas engine, low oil alert. Electric start standard on 11HP, 13HP and 20HP engines. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Head unloaders. Single stage: factory set at 90-125 PSI. Two stage: factory set at 140-175 PSI. Equipped with liquid filled gauge, snubber and flex hose. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty.

## CLIMATE CONTROL (HVAC) SERIES - SIMPLEX TANK MOUNTED SERIES

MODEL NO.	VOLTAGE	HP	DESCRIPTION
<b>CC-0530-01</b>	<b>115-230V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0530-01M</b>	<b>230V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-0530-010M</b>	<b>230V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0530-02</b>	<b>200-208V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0530-02M</b>	<b>200-208V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0530-020M</b>	<b>200-208V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0530-03</b>	<b>230-240V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0530-03M</b>	<b>230-240V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0530-030M</b>	<b>230-240V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0530-04</b>	<b>460-480V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-0530-04M</b>	<b>460-480V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0530-040M</b>	<b>460-480V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0530-05</b>	<b>575-600V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0530-05M</b>	<b>575-600V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0530-050M</b>	<b>575-600V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0530-115M</b>	<b>115V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0530-1150M</b>	<b>115V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-07530-01</b>	<b>115-230V/1PH</b>	<b>4</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-07530-01M</b>	<b>230V/1PH</b>	<b>4</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-07530-010M</b>	<b>230V/1PH</b>	<b>4</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-07530-02</b>	<b>200-208V/3PH</b>	<b>4</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-07530-02M</b>	<b>200-208V/3PH</b>	<b>4</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-07530-020M</b>	<b>200-208V/3PH</b>	<b>4</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-07530-03</b>	<b>230-240V/3PH</b>	<b>4</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-07530-03M</b>	<b>230-240V/3PH</b>	<b>4</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-07530-030M</b>	<b>230-240V/3PH</b>	<b>4</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-07530-04</b>	<b>460-480V/3PH</b>	<b>4</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 200 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-07530-04M</b>	<b>460-480V/3PH</b>	<b>4</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-07530-04OM</b>	<b>460-480V/3PH</b>	<b>4</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-07530-05</b>	<b>575-600V/3PH</b>	<b>4</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-07530-05M</b>	<b>575-600V/3PH</b>	<b>4</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-07530-05OM</b>	<b>575-600V/3PH</b>	<b>4</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-07530-115M</b>	<b>115V/1PH</b>	<b>4</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-07530-115OM</b>	<b>115V/1PH</b>	<b>4</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-0130-01</b>	<b>115-230V/1PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 200 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0130-01M</b>	<b>230V/1PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0130-010M</b>	<b>230V/1PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0130-02</b>	<b>200-208V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0130-02M</b>	<b>200-208V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0130-020M</b>	<b>200-208V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0130-03</b>	<b>230-240V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0130-03M</b>	<b>230-240V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-0130-030M</b>	<b>230-240V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 200 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0130-04</b>	<b>460-480V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0130-04M</b>	<b>460-480V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0130-040M</b>	<b>460-480V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0130-05</b>	<b>575-600V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0130-05M</b>	<b>575-600V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0130-050M</b>	<b>575-600V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0130-115M</b>	<b>115V/1PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-0130-1150M</b>	<b>115V/1PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0160-01</b>	<b>115-230V/1PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0160-01M</b>	<b>230V/1PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0160-010M</b>	<b>230V/1PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0160-02</b>	<b>200-208V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0160-02M</b>	<b>200-208V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0160-020M</b>	<b>200-208V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0160-03</b>	<b>230-240V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-0160-03M</b>	<b>230-240V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 200 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0160-030M</b>	<b>230-240V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0160-04</b>	<b>460-480V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0160-04M</b>	<b>460-480V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0160-040M</b>	<b>460-480V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0160-05</b>	<b>575-600V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 200 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0160-05M</b>	<b>575-600V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0160-050M</b>	<b>575-600V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-0160-115M</b>	<b>115V/1PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0160-1150M</b>	<b>115V/1PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-01530-01</b>	<b>115-230V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-01530-01M</b>	<b>230V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-01530-010M</b>	<b>230V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-01530-02</b>	<b>200-208V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-01530-02M</b>	<b>200-208V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-01530-020M</b>	<b>200-208V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-01530-03</b>	<b>230-240V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-01530-03M</b>	<b>230-240V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-01530-03OM</b>	<b>230-240V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-01530-04</b>	<b>460-480V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-01530-04M</b>	<b>460-480V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-01530-04OM</b>	<b>460-480V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-01530-05</b>	<b>575-600V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-01530-05M</b>	<b>575-600V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-01530-050M</b>	<b>575-600V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-01530-115M</b>	<b>115V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-01530-1150M</b>	<b>115V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-01560-01</b>	<b>230V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-01560-01M</b>	<b>230V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-01560-010M</b>	<b>230V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-01560-02</b>	<b>200-208V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-01560-02M</b>	<b>200-208V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-01560-020M</b>	<b>200-208V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 200 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-01560-03</b>	<b>230-240V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-01560-03M</b>	<b>230-240V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-01560-030M</b>	<b>230-240V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-01560-04</b>	<b>460-480V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-01560-04M</b>	<b>460-480V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-01560-040M</b>	<b>460-480V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-01560-05</b>	<b>575-600V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-01560-05M</b>	<b>575-600V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-01560-050M</b>	<b>575-600V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-01560-115M</b>	<b>230V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-01560-1150M</b>	<b>230V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0230-01</b>	<b>115-230V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0230-01M</b>	<b>230V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0230-010M</b>	<b>230V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0230-02</b>	<b>200-208V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-0230-02M</b>	<b>200-208V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 200 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0230-020M</b>	<b>200-208V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0230-03</b>	<b>230-240V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0230-03M</b>	<b>230-240V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0230-030M</b>	<b>230-240V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0230-04</b>	<b>460-480V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 200 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0230-04M</b>	<b>460-480V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0230-040M</b>	<b>460-480V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-0230-05</b>	<b>575-600V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 200 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0230-05M</b>	<b>575-600V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0230-050M</b>	<b>575-600V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0230-115M</b>	<b>115V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0230-1150M</b>	<b>115V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0260-01</b>	<b>115-230V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0260-01M</b>	<b>230V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0260-010M</b>	<b>230V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-0260-02</b>	<b>200-208V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 200 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0260-02M</b>	<b>200-208V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0260-020M</b>	<b>200-208V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0260-03</b>	<b>230-240V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0260-03M</b>	<b>230-240V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0260-030M</b>	<b>230-240V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0260-04</b>	<b>460-480V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0260-04M</b>	<b>460-480V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-0260-040M</b>	<b>460-480V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0260-05</b>	<b>575-600V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0260-05M</b>	<b>575-600V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0260-050M</b>	<b>575-600V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0260-115M</b>	<b>115-230V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0260-1150M</b>	<b>115-230V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0360-01</b>	<b>115-230V/1PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0360-01M</b>	<b>230V/1PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-0360-010M</b>	<b>230V/1PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0360-02</b>	<b>200-208V/3PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0360-02M</b>	<b>200-208V/3PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0360-020M</b>	<b>200-208V/3PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0360-03</b>	<b>230-240V/3PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0360-03M</b>	<b>230-240V/3PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0360-030M</b>	<b>230-240V/3PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0360-04</b>	<b>460-480V/3PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-0360-04M</b>	<b>460-480V/3PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 200 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0360-040M</b>	<b>460-480V/3PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0360-05</b>	<b>575-600V/3PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0360-05M</b>	<b>575-600V/3PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0360-050M</b>	<b>575-600V/3PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0360-115M</b>	<b>115V/1PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0360-1150M</b>	<b>115V/1PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0380-01</b>	<b>115-230V/1PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-0380-01M</b>	<b>230V/1PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0380-010M</b>	<b>230V/1PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0380-02</b>	<b>200-208V/3PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0380-02M</b>	<b>200-208V/3PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0380-020M</b>	<b>200-208V/3PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0380-03</b>	<b>230-240V/3PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0380-03M</b>	<b>230-240V/3PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0380-030M</b>	<b>230-240V/3PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-0380-04</b>	<b>460-480V/3PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 200 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0380-04M</b>	<b>460-480V/3PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0380-04OM</b>	<b>460-480V/3PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0380-05</b>	<b>575-600V/3PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0380-05M</b>	<b>575-600V/3PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0380-05OM</b>	<b>575-600V/3PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0380-115M</b>	<b>115V/1PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0380-115OM</b>	<b>115V/1PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-5080-01</b>	<b>230V/1PH</b>	<b>5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 200 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-5080-01M</b>	<b>230V/1PH</b>	<b>5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-5080-010M</b>	<b>230V/1PH</b>	<b>5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-5080-02</b>	<b>200-208V/3PH</b>	<b>5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-5080-02M</b>	<b>200-208V/3PH</b>	<b>5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-5080-020M</b>	<b>200-208V/3PH</b>	<b>5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-5080-03</b>	<b>230-240V/3PH</b>	<b>5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-5080-03M</b>	<b>230-240V/3PH</b>	<b>5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-5080-030M</b>	<b>230-240V/3PH</b>	<b>5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 200 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-5080-04</b>	<b>460-480V/3PH</b>	<b>5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-5080-04M</b>	<b>460-480V/3PH</b>	<b>5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-5080-040M</b>	<b>460-480V/3PH</b>	<b>5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-5080-05</b>	<b>575-600V/3PH</b>	<b>5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-5080-05M</b>	<b>575-600V/3PH</b>	<b>5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-5080-050M</b>	<b>575-600V/3PH</b>	<b>5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-50120-01</b>	<b>230V/1PH</b>	<b>5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-50120-01M</b>	<b>230V/1PH</b>	<b>5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-50120-010M</b>	<b>230V/1PH</b>	<b>5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-50120-02</b>	<b>200-208V/3PH</b>	<b>5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-50120-02M</b>	<b>200-208V/3PH</b>	<b>5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-50120-020M</b>	<b>200-208V/3PH</b>	<b>5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-50120-03</b>	<b>230-240V/3PH</b>	<b>5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-50120-03M</b>	<b>230-240V/3PH</b>	<b>5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-50120-030M</b>	<b>230-240V/3PH</b>	<b>5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-50120-04</b>	<b>460-480V/3PH</b>	<b>5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 200 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-50120-04M</b>	<b>460-480V/3PH</b>	<b>5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-50120-04OM</b>	<b>460-480V/3PH</b>	<b>5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-50120-05</b>	<b>575-600V/3PH</b>	<b>5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-50120-05M</b>	<b>575-600V/3PH</b>	<b>5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-50120-05OM</b>	<b>575-600V/3PH</b>	<b>5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-7580-02</b>	<b>200-208V/3PH</b>	<b>7.5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-7580-02M</b>	<b>200-208V/3PH</b>	<b>7.5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-7580-020M</b>	<b>200-208V/3PH</b>	<b>7.5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-7580-03</b>	<b>230-240V/3PH</b>	<b>7.5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-7580-03M</b>	<b>230-240V/3PH</b>	<b>7.5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-7580-030M</b>	<b>230-240V/3PH</b>	<b>7.5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-7580-04</b>	<b>460-480V/3PH</b>	<b>7.5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-7580-04M</b>	<b>460-480V/3PH</b>	<b>7.5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-7580-040M</b>	<b>460-480V/3PH</b>	<b>7.5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-7580-05</b>	<b>575-600V/3PH</b>	<b>7.5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-7580-05M</b>	<b>575-600V/3PH</b>	<b>7.5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-7580-050M</b>	<b>575-600V/3PH</b>	<b>7.5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-75120-02</b>	<b>200-208V/3PH</b>	<b>7.5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-75120-02M</b>	<b>200-208V/3PH</b>	<b>7.5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-75120-020M</b>	<b>200-208V/3PH</b>	<b>7.5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-75120-03</b>	<b>230-240V/3PH</b>	<b>7.5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-75120-03M</b>	<b>230-240V/3PH</b>	<b>7.5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-75120-030M</b>	<b>230-240V/3PH</b>	<b>7.5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-75120-04</b>	<b>460-480V/3PH</b>	<b>7.5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-75120-04M</b>	<b>460-480V/3PH</b>	<b>7.5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-75120-040M</b>	<b>460-480V/3PH</b>	<b>7.5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-75120-05</b>	<b>575-600V/3PH</b>	<b>7.5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-75120-05M</b>	<b>575-600V/3PH</b>	<b>7.5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-75120-050M</b>	<b>575-600V/3PH</b>	<b>7.5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-100120-02</b>	<b>200-208V/3PH</b>	<b>10</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-100120-02M</b>	<b>200-208V/3PH</b>	<b>10</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-100120-020M</b>	<b>200-208V/3PH</b>	<b>10</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 200 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-100120-03</b>	<b>230-240V/3PH</b>	<b>10</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-100120-03M</b>	<b>230-240V/3PH</b>	<b>10</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-100120-030M</b>	<b>230-240V/3PH</b>	<b>10</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-100120-04</b>	<b>460-480V/3PH</b>	<b>10</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-100120-04M</b>	<b>460-480V/3PH</b>	<b>10</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-100120-040M</b>	<b>460-480V/3PH</b>	<b>10</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-100120-05</b>	<b>575-600V/3PH</b>	<b>10</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-100120-05M</b>	<b>575-600V/3PH</b>	<b>10</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-100120-050M</b>	<b>575-600V/3PH</b>	<b>10</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-100240-02</b>	<b>200-208V/3PH</b>	<b>10</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-100240-02M</b>	<b>200-208V/3PH</b>	<b>10</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-100240-020M</b>	<b>200-208V/3PH</b>	<b>10</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-100240-03</b>	<b>230-240V/3PH</b>	<b>10</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-100240-03M</b>	<b>230-240V/3PH</b>	<b>10</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-100240-030M</b>	<b>230-240V/3PH</b>	<b>10</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-100240-04</b>	<b>460-480V/3PH</b>	<b>10</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-100240-04M</b>	<b>460-480V/3PH</b>	<b>10</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-100240-040M</b>	<b>460-480V/3PH</b>	<b>10</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-100240-05</b>	<b>575-600V/3PH</b>	<b>10</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-100240-05M</b>	<b>575-600V/3PH</b>	<b>10</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-100240-050M</b>	<b>575-600V/3PH</b>	<b>10</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-150240-02</b>	<b>200-208V/3PH</b>	<b>15</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-150240-02M</b>	<b>200-208V/3PH</b>	<b>15</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-150240-020M</b>	<b>200-208V/3PH</b>	<b>15</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 200 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-150240-03</b>	<b>230-240V/3PH</b>	<b>15</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-150240-03M</b>	<b>230-240V/3PH</b>	<b>15</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-150240-030M</b>	<b>230-240V/3PH</b>	<b>15</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-150240-04</b>	<b>460-480V/3PH</b>	<b>15</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-150240-04M</b>	<b>460-480V/3PH</b>	<b>15</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-150240-040M</b>	<b>460-480V/3PH</b>	<b>15</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-150240-05</b>	<b>575-600V/3PH</b>	<b>15</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-150240-05M</b>	<b>575-600V/3PH</b>	<b>15</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 200 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-150240-050M</b>	<b>575-600V/3PH</b>	<b>15</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-200240-02</b>	<b>200-208V/3PH</b>	<b>20</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-200240-02M</b>	<b>200-208V/3PH</b>	<b>20</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-200240-020M</b>	<b>200-208V/3PH</b>	<b>20</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-200240-03</b>	<b>230-240V/3PH</b>	<b>20</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-200240-03M</b>	<b>230-240V/3PH</b>	<b>20</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-200240-030M</b>	<b>230-240V/3PH</b>	<b>20</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-200240-04</b>	<b>460-480V/3PH</b>	<b>20</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-200240-04M</b>	<b>460-480V/3PH</b>	<b>20</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-200240-040M</b>	<b>460-480V/3PH</b>	<b>20</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-200240-05</b>	<b>575-600V/3PH</b>	<b>20</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-200240-05M</b>	<b>575-600V/3PH</b>	<b>20</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-200240-050M</b>	<b>575-600V/3PH</b>	<b>20</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-250240-02</b>	<b>200-208V/3PH</b>	<b>25</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-250240-02M</b>	<b>200-208V/3PH</b>	<b>25</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-250240-020M</b>	<b>200-208V/3PH</b>	<b>25</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 200 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-250240-03</b>	<b>230-240V/3PH</b>	<b>25</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-250240-03M</b>	<b>230-240V/3PH</b>	<b>25</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-250240-030M</b>	<b>230-240V/3PH</b>	<b>25</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-250240-04</b>	<b>460-480V/3PH</b>	<b>25</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-250240-04M</b>	<b>460-480V/3PH</b>	<b>25</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-250240-040M</b>	<b>460-480V/3PH</b>	<b>25</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-250240-05</b>	<b>575-600V/3PH</b>	<b>25</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-250240-05M</b>	<b>575-600V/3PH</b>	<b>25</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-250240-050M</b>	<b>575-600V/3PH</b>	<b>25</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-300240-02</b>	<b>200-208V/3PH</b>	<b>30</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-300240-02M</b>	<b>200-208V/3PH</b>	<b>30</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-300240-020M</b>	<b>200-208V/3PH</b>	<b>30</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-300240-03</b>	<b>230-240V/3PH</b>	<b>30</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-300240-03M</b>	<b>230-240V/3PH</b>	<b>30</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-300240-030M</b>	<b>230-240V/3PH</b>	<b>30</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-300240-04</b>	<b>460-480V/3PH</b>	<b>30</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-300240-04M</b>	<b>460-480V/3PH</b>	<b>30</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-300240-040M</b>	<b>460-480V/3PH</b>	<b>30</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-300240-05</b>	<b>575-600V/3PH</b>	<b>30</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-300240-05M</b>	<b>575-600V/3PH</b>	<b>30</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-300240-050M</b>	<b>575-600V/3PH</b>	<b>30</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

## CLIMATE CONTROL (HVAC) SERIES - BASE MOUNTED SERIES

MODEL NO.	VOLTAGE	HP	DESCRIPTION
<b>CC-0500-01</b>	<b>115-230V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-0500-01M</b>	<b>230V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0500-010M</b>	<b>230V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0500-02</b>	<b>200-208V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0500-02M</b>	<b>200-208V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0500-020M</b>	<b>200-208V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0500-03</b>	<b>200-240V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0500-03M</b>	<b>200-240V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0500-030M</b>	<b>200-240V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-0500-04</b>	<b>460-480V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0500-04M</b>	<b>460-480V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0500-040M</b>	<b>460-480V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0500-05</b>	<b>575-600V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0500-05M</b>	<b>575-600V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0500-050M</b>	<b>575-600V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0500-115M</b>	<b>115V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0500-1150M</b>	<b>115V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-07500-01</b>	<b>115-230V/1PH</b>	<b>4</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-07500-01M</b>	<b>230V/1PH</b>	<b>4</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-07500-010M</b>	<b>230V/1PH</b>	<b>4</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-07500-02</b>	<b>200-208V/3PH</b>	<b>4</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-07500-02M</b>	<b>200-208V/3PH</b>	<b>4</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-07500-020M</b>	<b>200-208V/3PH</b>	<b>4</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-07500-03</b>	<b>200-240V/3PH</b>	<b>4</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-07500-03M</b>	<b>200-240V/3PH</b>	<b>4</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-07500-030M</b>	<b>200-240V/3PH</b>	<b>4</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-07500-04</b>	<b>460-480V/3PH</b>	<b>4</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-07500-04M</b>	<b>460-480V/3PH</b>	<b>4</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-07500-040M</b>	<b>460-480V/3PH</b>	<b>4</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-07500-05</b>	<b>575-600V/3PH</b>	<b>4</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-07500-05M</b>	<b>575-600V/3PH</b>	<b>4</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-07500-050M</b>	<b>575-600V/3PH</b>	<b>4</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-07500-115M</b>	<b>115V/1PH</b>	<b>4</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-07500-1150M</b>	<b>115V/1PH</b>	<b>4</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0100-01</b>	<b>115-230V/1PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0100-01M</b>	<b>230V/1PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0100-010M</b>	<b>230V/1PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0100-02</b>	<b>200-208V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0100-02M</b>	<b>200-208V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0100-020M</b>	<b>200-208V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0100-03</b>	<b>200-240V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-0100-03M</b>	<b>200-240V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0100-030M</b>	<b>200-240V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0100-04</b>	<b>460-480V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0100-04M</b>	<b>460-480V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0100-040M</b>	<b>460-480V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0100-05</b>	<b>575-600V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0100-05M</b>	<b>575-600V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0100-050M</b>	<b>575-600V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-0100-115M</b>	<b>115V/1PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0100-1150M</b>	<b>115V/1PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-01500-01</b>	<b>115-230V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-01500-01M</b>	<b>230V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-01500-010M</b>	<b>230V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-01500-02</b>	<b>200-208V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-01500-02M</b>	<b>200-208V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-01500-020M</b>	<b>200-208V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-01500-03</b>	<b>230-240V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-01500-03M</b>	<b>230-240V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-01500-03OM</b>	<b>230-240V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-01500-04</b>	<b>460-480V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-01500-04M</b>	<b>460-480V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-01500-04OM</b>	<b>460-480V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-01500-05</b>	<b>575-600V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-01500-05M</b>	<b>575-600V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-01500-050M</b>	<b>575-600V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-01500-115M</b>	<b>115V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-01500-1150M</b>	<b>115V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0200-01</b>	<b>115-230V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0200-01M</b>	<b>230V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0200-010M</b>	<b>230V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0200-02</b>	<b>200-208V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0200-02M</b>	<b>200-208V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-0200-020M</b>	<b>200-208V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0200-03</b>	<b>230-240V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0200-03M</b>	<b>230-240V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0200-030M</b>	<b>230-240V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0200-04</b>	<b>460-480V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0200-04M</b>	<b>460-480V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0200-040M</b>	<b>460-480V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0200-05</b>	<b>575-600V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-0200-05M</b>	<b>575-600V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0200-050M</b>	<b>575-600V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0200-115M</b>	<b>115V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0200-1150M</b>	<b>115V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0300-01</b>	<b>115-230V/1PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0300-01M</b>	<b>230V/1PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0300-010M</b>	<b>230V/1PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0300-02</b>	<b>200-208V/3PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-0300-02M</b>	<b>200-208V/3PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0300-020M</b>	<b>200-208V/3PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0300-03</b>	<b>230-240V/3PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0300-03M</b>	<b>230-240V/3PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0300-030M</b>	<b>230-240V/3PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0300-04</b>	<b>460-480V/3PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0300-04M</b>	<b>460-480V/3PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0300-040M</b>	<b>460-480V/3PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-0300-05</b>	<b>575-600V/3PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0300-05M</b>	<b>575-600V/3PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0300-050M</b>	<b>575-600V/3PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0300-115M</b>	<b>115V/1PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-0300-1150M</b>	<b>115V/1PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-5000-01</b>	<b>230V/1PH</b>	<b>5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-5000-01M</b>	<b>230V/1PH</b>	<b>5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-5000-010M</b>	<b>230V/1PH</b>	<b>5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-5000-02</b>	<b>200-208V/3PH</b>	<b>5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-5000-02M</b>	<b>200-208V/3PH</b>	<b>5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-5000-02OM</b>	<b>200-208V/3PH</b>	<b>5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-5000-03</b>	<b>230-240V/3PH</b>	<b>5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-5000-03M</b>	<b>230-240V/3PH</b>	<b>5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-5000-03OM</b>	<b>230-240V/3PH</b>	<b>5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-5000-04</b>	<b>460-480V/3PH</b>	<b>5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-5000-04M</b>	<b>460-480V/3PH</b>	<b>5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-5000-040M</b>	<b>460-480V/3PH</b>	<b>5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-5000-05</b>	<b>575-600V/3PH</b>	<b>5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-5000-05M</b>	<b>575-600V/3PH</b>	<b>5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-5000-050M</b>	<b>575-600V/3PH</b>	<b>5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-7500-02</b>	<b>200-208V/3PH</b>	<b>7.5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-7500-02M</b>	<b>200-208V/3PH</b>	<b>7.5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-7500-020M</b>	<b>200-208V/3PH</b>	<b>7.5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-7500-03</b>	<b>230-240V/3PH</b>	<b>7.5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-7500-03M</b>	<b>230-240V/3PH</b>	<b>7.5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-7500-030M</b>	<b>230-240V/3PH</b>	<b>7.5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-7500-04</b>	<b>460-480V/3PH</b>	<b>7.5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-7500-04M</b>	<b>460-480V/3PH</b>	<b>7.5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-7500-040M</b>	<b>460-480V/3PH</b>	<b>7.5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-7500-05</b>	<b>575-600V/3PH</b>	<b>7.5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-7500-05M</b>	<b>575-600V/3PH</b>	<b>7.5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-7500-050M</b>	<b>575-600V/3PH</b>	<b>7.5</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-100000-02</b>	<b>200-208V/3PH</b>	<b>10</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-100000-02M</b>	<b>200-208V/3PH</b>	<b>10</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-100000-02OM</b>	<b>200-208V/3PH</b>	<b>10</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-100000-03</b>	<b>230-240V/3PH</b>	<b>10</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-100000-03M</b>	<b>230-240V/3PH</b>	<b>10</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-100000-03OM</b>	<b>230-240V/3PH</b>	<b>10</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-100000-04</b>	<b>460-480V/3PH</b>	<b>10</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-100000-04M</b>	<b>460-480V/3PH</b>	<b>10</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-100000-040M</b>	<b>460-480V/3PH</b>	<b>10</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-100000-05</b>	<b>575-600V/3PH</b>	<b>10</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-100000-05M</b>	<b>575-600V/3PH</b>	<b>10</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-100000-050M</b>	<b>575-600V/3PH</b>	<b>10</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-150000-02</b>	<b>200-208V/3PH</b>	<b>15</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-150000-02M</b>	<b>200-208V/3PH</b>	<b>15</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-150000-020M</b>	<b>200-208V/3PH</b>	<b>15</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-150000-03</b>	<b>230-240V/3PH</b>	<b>15</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-150000-03M</b>	<b>230-240V/3PH</b>	<b>15</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-150000-030M</b>	<b>230-240V/3PH</b>	<b>15</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-150000-04</b>	<b>460-480V/3PH</b>	<b>15</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-150000-04M</b>	<b>460-480V/3PH</b>	<b>15</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-150000-040M</b>	<b>460-480V/3PH</b>	<b>15</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-150000-05</b>	<b>575-600V/3PH</b>	<b>15</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-150000-05M</b>	<b>575-600V/3PH</b>	<b>15</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-150000-050M</b>	<b>575-600V/3PH</b>	<b>15</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-200000-02</b>	<b>200-208V/3PH</b>	<b>20</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-200000-02M</b>	<b>200-208V/3PH</b>	<b>20</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-200000-02OM</b>	<b>200-208V/3PH</b>	<b>20</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-200000-03</b>	<b>230-240V/3PH</b>	<b>20</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-200000-03M</b>	<b>230-240V/3PH</b>	<b>20</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-200000-03OM</b>	<b>230-240V/3PH</b>	<b>20</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-200000-04</b>	<b>460-480V/3PH</b>	<b>20</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-200000-04M</b>	<b>460-480V/3PH</b>	<b>20</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-200000-040M</b>	<b>460-480V/3PH</b>	<b>20</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-200000-05</b>	<b>575-600V/3PH</b>	<b>20</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-200000-05M</b>	<b>575-600V/3PH</b>	<b>20</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-200000-050M</b>	<b>575-600V/3PH</b>	<b>20</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-250000-02</b>	<b>200-208V/3PH</b>	<b>25</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-250000-02M</b>	<b>200-208V/3PH</b>	<b>25</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-250000-020M</b>	<b>200-208V/3PH</b>	<b>25</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-250000-03</b>	<b>230-240V/3PH</b>	<b>25</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-250000-03M</b>	<b>230-240V/3PH</b>	<b>25</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-250000-03OM</b>	<b>230-240V/3PH</b>	<b>25</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-250000-04</b>	<b>460-480V/3PH</b>	<b>25</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-250000-04M</b>	<b>460-480V/3PH</b>	<b>25</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-250000-04OM</b>	<b>460-480V/3PH</b>	<b>25</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-250000-05</b>	<b>575-600V/3PH</b>	<b>25</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-250000-05M</b>	<b>575-600V/3PH</b>	<b>25</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-250000-05OM</b>	<b>575-600V/3PH</b>	<b>25</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-300000-02</b>	<b>200-208V/3PH</b>	<b>30</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-300000-02M</b>	<b>200-208V/3PH</b>	<b>30</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-300000-02OM</b>	<b>200-208V/3PH</b>	<b>30</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-300000-03</b>	<b>230-240V/3PH</b>	<b>30</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-300000-03M</b>	<b>230-240V/3PH</b>	<b>30</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-300000-03OM</b>	<b>230-240V/3PH</b>	<b>30</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-300000-04</b>	<b>460-480V/3PH</b>	<b>30</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-300000-04M</b>	<b>460-480V/3PH</b>	<b>30</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-300000-040M</b>	<b>460-480V/3PH</b>	<b>30</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-300000-05</b>	<b>575-600V/3PH</b>	<b>30</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-300000-05M</b>	<b>575-600V/3PH</b>	<b>30</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-300000-050M</b>	<b>575-600V/3PH</b>	<b>30</b>	Heavy duty single and two stage high efficiency cast iron air compressor. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Equipped with liquid filled gauge, snubber and flex hose. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

## CLIMATE CONTROL (HVAC) SERIES - DUPLEX SERIES

<b>MODEL NO.</b>	<b>VOLTAGE</b>	<b>HP</b>	<b>DESCRIPTION</b>
<b>CC-DX-0530-01</b>	<b>115-230V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0530-01ALT</b>	<b>230V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0530-01OALT</b>	<b>230V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-DX-0530-02</b>	<b>200-208V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0530-02ALT</b>	<b>200-208V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0530-02OALT</b>	<b>200-208V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0530-03</b>	<b>230-240V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0530-03ALT</b>	<b>230-240V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0530-03OALT</b>	<b>230-240V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0530-04</b>	<b>460-480V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0530-04ALT</b>	<b>460-480V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-DX-0530-04OALT</b>	<b>460-480V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0530-05</b>	<b>575-600V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0530-05ALT</b>	<b>575-600V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0530-05OALT</b>	<b>575-600V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0530-115ALT</b>	<b>115V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0530-115OALT</b>	<b>115V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0560-01</b>	<b>115-230V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0560-01ALT</b>	<b>230V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-DX-0560-01OALT</b>	<b>230V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0560-02</b>	<b>200-208V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0560-02ALT</b>	<b>200-208V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0560-02OALT</b>	<b>200-208V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0560-03</b>	<b>230-240V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0560-03ALT</b>	<b>230-240V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0560-03OALT</b>	<b>230-240V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0560-04</b>	<b>460-480V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-DX-0560-04ALT</b>	<b>460-480V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0560-04OALT</b>	<b>460-480V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0560-05</b>	<b>575-600V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0560-05ALT</b>	<b>575-600V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0560-05OALT</b>	<b>575-600V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0560-115ALT</b>	<b>115V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0560-115OALT</b>	<b>115V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-07530-01</b>	<b>115-230V/1PH</b>	<b>4</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

CC-DX-07530-01ALT	230V/1PH	4	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
CC-DX-07530-010ALT	230V/1PH	4	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
CC-DX-07530-02	200-208V/3PH	4	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
CC-DX-07530-02ALT	200-208V/3PH	4	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
CC-DX-07530-020ALT	200-208V/3PH	4	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
CC-DX-07530-03	230-240V/3PH	4	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
CC-DX-07530-03ALT	230-240V/3PH	4	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
CC-DX-07530-030ALT	230-240V/3PH	4	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-DX-07530-04</b>	<b>460-480V/3PH</b>	<b>4</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-07530-04ALT</b>	<b>460-480V/3PH</b>	<b>4</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-07530-04OALT</b>	<b>460-480V/3PH</b>	<b>4</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-07530-05</b>	<b>575-600V/3PH</b>	<b>4</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-07530-05ALT</b>	<b>575-600V/3PH</b>	<b>4</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-07530-05OALT</b>	<b>575-600V/3PH</b>	<b>4</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-07530-115ALT</b>	<b>115V/1PH</b>	<b>4</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-07530-115OALT</b>	<b>115V/1PH</b>	<b>4</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-DX-07560-01</b>	<b>115-230V/1PH</b>	<b>4</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-07560-01ALT</b>	<b>230V/1PH</b>	<b>4</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-07560-01OALT</b>	<b>230V/1PH</b>	<b>4</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-07560-02</b>	<b>200-208V/3PH</b>	<b>4</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-07560-02ALT</b>	<b>200-208V/3PH</b>	<b>4</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-07560-02OALT</b>	<b>200-208V/3PH</b>	<b>4</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-07560-03</b>	<b>230-240V/3PH</b>	<b>4</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-07560-03ALT</b>	<b>230-240V/3PH</b>	<b>4</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-DX-07560-03OALT</b>	<b>230-240V/3PH</b>	<b>4</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-07560-04</b>	<b>460-480V/3PH</b>	<b>4</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-07560-04ALT</b>	<b>460-480V/3PH</b>	<b>4</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-07560-04OALT</b>	<b>460-480V/3PH</b>	<b>4</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-07560-05</b>	<b>575-600V/3PH</b>	<b>4</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-07560-05ALT</b>	<b>575-600V/3PH</b>	<b>4</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-07560-05OALT</b>	<b>575-600V/3PH</b>	<b>4</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-07560-115ALT</b>	<b>115V/1PH</b>	<b>4</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

CC-DX-07560-1150ALT	115V/1PH	4	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
CC-DX-07580-01	115-230V/1PH	4	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
CC-DX-07580-01ALT	230V/1PH	4	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
CC-DX-07580-010ALT	230V/1PH	4	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
CC-DX-07580-02	200-208V/3PH	4	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
CC-DX-07580-02ALT	200-208V/3PH	4	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
CC-DX-07580-020ALT	200-208V/3PH	4	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
CC-DX-07580-03	230-240V/3PH	4	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

CC-DX-07580-03ALT	230-240V/3PH	4	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
CC-DX-07580-03OALT	230-240V/3PH	4	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
CC-DX-07580-04	460-480V/3PH	4	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
CC-DX-07580-04ALT	460-480V/3PH	4	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
CC-DX-07580-04OALT	460-480V/3PH	4	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
CC-DX-07580-05	575-600V/3PH	4	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
CC-DX-07580-05ALT	575-600V/3PH	4	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
CC-DX-07580-05OALT	575-600V/3PH	4	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-DX-07580-115ALT</b>	<b>115V/1PH</b>	<b>4</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-07580-115OALT</b>	<b>115V/1PH</b>	<b>4</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0130-01</b>	<b>230V/1PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0130-01ALT</b>	<b>230V/1PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0130-01OALT</b>	<b>230V/1PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0130-02</b>	<b>200-208V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0130-02ALT</b>	<b>200-208V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0130-02OALT</b>	<b>200-208V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-DX-0130-03</b>	<b>230-240V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0130-03ALT</b>	<b>230-240V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0130-03OALT</b>	<b>230-240V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0130-04</b>	<b>460-480V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0130-04ALT</b>	<b>460-480V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0130-04OALT</b>	<b>460-480V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0130-05</b>	<b>575-600V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0130-05ALT</b>	<b>575-600V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-DX-0130-050ALT</b>	<b>575-600V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0130-115ALT</b>	<b>115V/1PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0130-1150ALT</b>	<b>115V/1PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0160-01</b>	<b>115-230V/1PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0160-01ALT</b>	<b>230V/1PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0160-010ALT</b>	<b>230V/1PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0160-02</b>	<b>200-208V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0160-02ALT</b>	<b>200-208V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-DX-0160-02OALT</b>	<b>200-208V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0160-03</b>	<b>230-240V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0160-03ALT</b>	<b>230-240V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0160-03OALT</b>	<b>230-240V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0160-04</b>	<b>460-480V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0160-04ALT</b>	<b>460-480V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0160-04OALT</b>	<b>460-480V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0160-05</b>	<b>575-600V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-DX-0160-05ALT</b>	<b>575-600V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0160-05OALT</b>	<b>575-600V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0160-115ALT</b>	<b>115V/1PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0160-115OALT</b>	<b>115V/1PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0180-01</b>	<b>115-230V/1PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0180-01ALT</b>	<b>230V/1PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0180-01OALT</b>	<b>230V/1PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0180-02</b>	<b>200-208V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-DX-0180-02ALT</b>	<b>200-208V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0180-02OALT</b>	<b>200-208V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0180-03</b>	<b>230-240V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0180-03ALT</b>	<b>230-240V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0180-03OALT</b>	<b>230-240V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0180-04</b>	<b>460-480V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0180-04ALT</b>	<b>460-480V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0180-04OALT</b>	<b>460-480V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-DX-0180-05</b>	<b>575-600V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0180-05ALT</b>	<b>575-600V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0180-05OALT</b>	<b>575-600V/3PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0180-115ALT</b>	<b>115V/1PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0180-115OALT</b>	<b>115V/1PH</b>	<b>1</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-01530-01</b>	<b>115-230V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-01530-01ALT</b>	<b>230V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-01530-01OALT</b>	<b>230V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-DX-01530-02</b>	<b>200-208V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-01530-02ALT</b>	<b>200-208V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-01530-02OALT</b>	<b>200-208V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-01530-03</b>	<b>230-240V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-01530-03ALT</b>	<b>230-240V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-01530-03OALT</b>	<b>230-240V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-01530-04</b>	<b>460-480V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-01530-04ALT</b>	<b>460-480V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-DX-01530-04OALT</b>	<b>460-480V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-01530-05</b>	<b>575-600V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-01530-05ALT</b>	<b>575-600V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-01530-05OALT</b>	<b>575-600V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-01530-115ALT</b>	<b>115V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-01530-115OALT</b>	<b>115V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-01560-01</b>	<b>230V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-01560-01ALT</b>	<b>230V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-DX-01560-01OALT</b>	<b>230V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-01560-02</b>	<b>200-208V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-01560-02ALT</b>	<b>200-208V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-01560-02OALT</b>	<b>200-208V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-01560-03</b>	<b>230-240V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-01560-03ALT</b>	<b>230-240V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-01560-03OALT</b>	<b>230-240V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-01560-04</b>	<b>460-480V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

CC-DX-01560-04ALT	460-480V/3PH	2	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
CC-DX-01560-04OALT	460-480V/3PH	2	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
CC-DX-01560-05	575-600V/3PH	2	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
CC-DX-01560-05ALT	575-600V/3PH	2	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
CC-DX-01560-05OALT	575-600V/3PH	2	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
CC-DX-01560-115ALT	230V/1PH	2	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
CC-DX-01560-115OALT	230V/1PH	2	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
CC-DX-01580-01	230V/1PH	2	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-DX-01580-01ALT</b>	<b>230V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-01580-01OALT</b>	<b>230V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-01580-02</b>	<b>200-208V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-01580-02ALT</b>	<b>200-208V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-01580-02OALT</b>	<b>200-208V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-01580-03</b>	<b>230-240V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-01580-03ALT</b>	<b>230-240V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-01580-03OALT</b>	<b>230-240V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-DX-01580-04</b>	<b>460-480V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-01580-04ALT</b>	<b>460-480V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-01580-04OALT</b>	<b>460-480V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-01580-05</b>	<b>575-600V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-01580-05ALT</b>	<b>575-600V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-01580-05OALT</b>	<b>575-600V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-01580-115ALT</b>	<b>230V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-01580-115OALT</b>	<b>230V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

CC-DX-0230-01	115-230V/1PH	2	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
CC-DX-0230-01ALT	230V/1PH	2	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
CC-DX-0230-01OALT	230V/1PH	2	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
CC-DX-0230-02	200-208V/3PH	2	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
CC-DX-0230-02ALT	200-208V/3PH	2	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
CC-DX-0230-02OALT	200-208V/3PH	2	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
CC-DX-0230-03	230-240V/3PH	2	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
CC-DX-0230-03ALT	230-240V/3PH	2	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-DX-0230-03OALT</b>	<b>230-240V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0230-04</b>	<b>460-480V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0230-04OALT</b>	<b>460-480V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0230-04OALT</b>	<b>460-480V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0230-05</b>	<b>575-600V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0230-05OALT</b>	<b>575-600V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0230-05OALT</b>	<b>575-600V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0230-115OALT</b>	<b>115V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-DX-0230-1150ALT</b>	<b>115V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0260-01</b>	<b>115-230V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0260-01ALT</b>	<b>230V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0260-01OALT</b>	<b>230V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0260-02</b>	<b>200-208V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0260-02ALT</b>	<b>200-208V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0260-02OALT</b>	<b>200-208V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0260-03</b>	<b>230-240V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-DX-0260-03ALT</b>	<b>230-240V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0260-03OALT</b>	<b>230-240V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0260-04</b>	<b>460-480V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0260-04ALT</b>	<b>460-480V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0260-04OALT</b>	<b>460-480V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0260-05</b>	<b>575-600V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0260-05ALT</b>	<b>575-600V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0260-05OALT</b>	<b>575-600V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-DX-0260-115ALT</b>	<b>115-230V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0260-1150ALT</b>	<b>115-230V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0280-01</b>	<b>115-230V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0280-01ALT</b>	<b>230V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0280-010ALT</b>	<b>230V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0280-02</b>	<b>200-208V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0280-02ALT</b>	<b>200-208V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0280-020ALT</b>	<b>200-208V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-DX-0280-03</b>	<b>230-240V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0280-03ALT</b>	<b>230-240V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0280-03OALT</b>	<b>230-240V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0280-04</b>	<b>460-480V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0280-04ALT</b>	<b>460-480V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0280-04OALT</b>	<b>460-480V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0280-05</b>	<b>575-600V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0280-05ALT</b>	<b>575-600V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-DX-0280-050ALT</b>	<b>575-600V/3PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0280-115ALT</b>	<b>115-230V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0280-1150ALT</b>	<b>115-230V/1PH</b>	<b>2</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-03120-01</b>	<b>115-230V/1PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-03120-01ALT</b>	<b>230V/1PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-03120-010ALT</b>	<b>230V/1PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-03120-02</b>	<b>200-208V/3PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-03120-02ALT</b>	<b>200-208V/3PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-DX-03120-02OALT</b>	<b>200-208V/3PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-03120-03</b>	<b>230-240V/3PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-03120-03ALT</b>	<b>230-240V/3PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-03120-03OALT</b>	<b>230-240V/3PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-03120-04</b>	<b>460-480V/3PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-03120-04ALT</b>	<b>460-480V/3PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-03120-04OALT</b>	<b>460-480V/3PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-03120-05</b>	<b>575-600V/3PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

CC-DX-03120-05ALT	575-600V/3PH	3	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
CC-DX-03120-050ALT	575-600V/3PH	3	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
CC-DX-03120-115ALT	115V/1PH	3	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
CC-DX-03120-1150ALT	115V/1PH	3	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
CC-DX-0380-01	115-230V/1PH	3	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
CC-DX-0380-01ALT	230V/1PH	3	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
CC-DX-0380-010ALT	230V/1PH	3	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
CC-DX-0380-02	200-208V/3PH	3	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-DX-0380-02ALT</b>	<b>200-208V/3PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0380-02OALT</b>	<b>200-208V/3PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0380-03</b>	<b>230-240V/3PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0380-03ALT</b>	<b>230-240V/3PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0380-03OALT</b>	<b>230-240V/3PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0380-04</b>	<b>460-480V/3PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0380-04ALT</b>	<b>460-480V/3PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0380-04OALT</b>	<b>460-480V/3PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-DX-0380-05</b>	<b>575-600V/3PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0380-05ALT</b>	<b>575-600V/3PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0380-05OALT</b>	<b>575-600V/3PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0380-115ALT</b>	<b>115V/1PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-0380-115OALT</b>	<b>115V/1PH</b>	<b>3</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-50120-01</b>	<b>230V/1PH</b>	<b>5</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-50120-01ALT</b>	<b>230V/1PH</b>	<b>5</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-50120-01OALT</b>	<b>230V/1PH</b>	<b>5</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-DX-50120-02</b>	<b>200-208V/3PH</b>	<b>5</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-50120-02ALT</b>	<b>200-208V/3PH</b>	<b>5</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-50120-02OALT</b>	<b>200-208V/3PH</b>	<b>5</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-50120-03</b>	<b>230-240V/3PH</b>	<b>5</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-50120-03ALT</b>	<b>230-240V/3PH</b>	<b>5</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-50120-03OALT</b>	<b>230-240V/3PH</b>	<b>5</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-50120-04</b>	<b>460-480V/3PH</b>	<b>5</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-50120-04ALT</b>	<b>460-480V/3PH</b>	<b>5</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-DX-50120-040ALT</b>	<b>460-480V/3PH</b>	<b>5</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-50120-05</b>	<b>575-600V/3PH</b>	<b>5</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-50120-05ALT</b>	<b>575-600V/3PH</b>	<b>5</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-50120-050ALT</b>	<b>575-600V/3PH</b>	<b>5</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-75120-02</b>	<b>200-208V/3PH</b>	<b>7.5</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-75120-02ALT</b>	<b>200-208V/3PH</b>	<b>7.5</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-75120-020ALT</b>	<b>200-208V/3PH</b>	<b>7.5</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-75120-03</b>	<b>230-240V/3PH</b>	<b>7.5</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

CC-DX-75120-03ALT	230-240V/3PH	7.5	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
CC-DX-75120-030ALT	230-240V/3PH	7.5	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
CC-DX-75120-04	460-480V/3PH	7.5	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
CC-DX-75120-04ALT	460-480V/3PH	7.5	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
CC-DX-75120-040ALT	460-480V/3PH	7.5	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
CC-DX-75120-05	575-600V/3PH	7.5	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
CC-DX-75120-05ALT	575-600V/3PH	7.5	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
CC-DX-75120-050ALT	575-600V/3PH	7.5	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-DX-75240-02</b>	<b>200-208V/3PH</b>	<b>7.5</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-75240-02ALT</b>	<b>200-208V/3PH</b>	<b>7.5</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-75240-02OALT</b>	<b>200-208V/3PH</b>	<b>7.5</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-75240-03</b>	<b>230-240V/3PH</b>	<b>7.5</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-75240-03ALT</b>	<b>230-240V/3PH</b>	<b>7.5</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-75240-03OALT</b>	<b>230-240V/3PH</b>	<b>7.5</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-75240-04</b>	<b>460-480V/3PH</b>	<b>7.5</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-75240-04ALT</b>	<b>460-480V/3PH</b>	<b>7.5</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-DX-75240-04OALT</b>	<b>460-480V/3PH</b>	<b>7.5</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-75240-05</b>	<b>575-600V/3PH</b>	<b>7.5</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-75240-05ALT</b>	<b>575-600V/3PH</b>	<b>7.5</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-75240-05OALT</b>	<b>575-600V/3PH</b>	<b>7.5</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-100120-02</b>	<b>200-208V/3PH</b>	<b>10</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-100120-02ALT</b>	<b>200-208V/3PH</b>	<b>10</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-100120-02OALT</b>	<b>200-208V/3PH</b>	<b>10</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-100120-03</b>	<b>230-240V/3PH</b>	<b>10</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-DX-100120-03ALT</b>	<b>230-240V/3PH</b>	<b>10</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-100120-03OALT</b>	<b>230-240V/3PH</b>	<b>10</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-100120-04</b>	<b>460-480V/3PH</b>	<b>10</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-100120-04ALT</b>	<b>460-480V/3PH</b>	<b>10</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-100120-04OALT</b>	<b>460-480V/3PH</b>	<b>10</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-100120-05</b>	<b>575-600V/3PH</b>	<b>10</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-100120-05ALT</b>	<b>575-600V/3PH</b>	<b>10</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-100120-05OALT</b>	<b>575-600V/3PH</b>	<b>10</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-DX-100240-02</b>	<b>200-208V/3PH</b>	<b>10</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-100240-02ALT</b>	<b>200-208V/3PH</b>	<b>10</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-100240-02OALT</b>	<b>200-208V/3PH</b>	<b>10</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-100240-03</b>	<b>230-240V/3PH</b>	<b>10</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-100240-03ALT</b>	<b>230-240V/3PH</b>	<b>10</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-100240-03OALT</b>	<b>230-240V/3PH</b>	<b>10</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-100240-04</b>	<b>460-480V/3PH</b>	<b>10</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-100240-04ALT</b>	<b>460-480V/3PH</b>	<b>10</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-DX-100240-040ALT</b>	<b>460-480V/3PH</b>	<b>10</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-100240-05</b>	<b>575-600V/3PH</b>	<b>10</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-100240-05ALT</b>	<b>575-600V/3PH</b>	<b>10</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-100240-050ALT</b>	<b>575-600V/3PH</b>	<b>10</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-150240-02</b>	<b>200-208V/3PH</b>	<b>15</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-150240-02ALT</b>	<b>200-208V/3PH</b>	<b>15</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-150240-020ALT</b>	<b>200-208V/3PH</b>	<b>15</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-150240-03</b>	<b>230-240V/3PH</b>	<b>15</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

<b>CC-DX-150240-03ALT</b>	<b>230-240V/3PH</b>	<b>15</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-150240-03OALT</b>	<b>230-240V/3PH</b>	<b>15</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-150240-04</b>	<b>460-480V/3PH</b>	<b>15</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-150240-04ALT</b>	<b>460-480V/3PH</b>	<b>15</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-150240-04OALT</b>	<b>460-480V/3PH</b>	<b>15</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-150240-05</b>	<b>575-600V/3PH</b>	<b>15</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-150240-05ALT</b>	<b>575-600V/3PH</b>	<b>15</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.
<b>CC-DX-150240-05OALT</b>	<b>575-600V/3PH</b>	<b>15</b>	Heavy duty single and two stage high efficiency cast iron air compressor, duplex configuration. Low pump RPM for less oil carryover, longevity and durability. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Rigid base motor, continuous duty, 1800 RPM, ODP. Factory set at 70-90 PSI with heavy duty pressure switch. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Alternator control panel available (supplied loose). Extended drain valve. Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. For climate control, laboratories and dental clinic applications.

## OIL FREE SERIES - SIMPLEX TANK MOUNTED SERIES

MODEL NO.	VOLTAGE	HP	DESCRIPTION
<b>BF-0220-01</b>	<b>115-230V/1PH</b>	<b>2</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-0220-01M</b>	<b>230V/1PH</b>	<b>2</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-0230-01</b>	<b>115-230V/1PH</b>	<b>2</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-0230-01M</b>	<b>230V/1PH</b>	<b>2</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-0230-02</b>	<b>200-208V/3PH</b>	<b>2</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-0230-02M</b>	<b>200-208V/3PH</b>	<b>2</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-0230-03</b>	<b>230-240V/3PH</b>	<b>2</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.

<b>BF-0230-03M</b>	<b>230-240V/3PH</b>	<b>2</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-0230-04</b>	<b>460-480V/3PH</b>	<b>2</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-0230-04M</b>	<b>460-480V/3PH</b>	<b>2</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-0230-05</b>	<b>575-600V/3PH</b>	<b>2</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-0230-05M</b>	<b>575-600V/3PH</b>	<b>2</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-0230-115M</b>	<b>115V/1PH</b>	<b>2</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-0260-01</b>	<b>115-230V/1PH</b>	<b>2</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-0260-01M</b>	<b>230V/1PH</b>	<b>2</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.

<b>BF-0260-02</b>	<b>200-208V/3PH</b>	<b>2</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-0260-02M</b>	<b>200-208V/3PH</b>	<b>2</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-0260-03</b>	<b>230-240V/3PH</b>	<b>2</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-0260-03M</b>	<b>230-240V/3PH</b>	<b>2</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-0260-04</b>	<b>460-480V/3PH</b>	<b>2</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-0260-04M</b>	<b>460-480V/3PH</b>	<b>2</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-0260-05</b>	<b>575-600V/3PH</b>	<b>2</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-0260-05M</b>	<b>575-600V/3PH</b>	<b>2</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.

<b>BF-0260-115M</b>	<b>115-230V/1PH</b>	<b>2</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-0360-01</b>	<b>115-230V/1PH</b>	<b>3</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-0360-01M</b>	<b>230V/1PH</b>	<b>3</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-0360-02</b>	<b>200-208V/3PH</b>	<b>3</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-0360-02M</b>	<b>200-208V/3PH</b>	<b>3</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-0360-03</b>	<b>230-240V/3PH</b>	<b>3</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-0360-03M</b>	<b>230-240V/3PH</b>	<b>3</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-0360-04</b>	<b>460-480V/3PH</b>	<b>3</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.

<b>BF-0360-04M</b>	<b>460-480V/3PH</b>	<b>3</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-0360-05</b>	<b>575-600V/3PH</b>	<b>3</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-0360-05M</b>	<b>575-600V/3PH</b>	<b>3</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-0360-115M</b>	<b>115V/1PH</b>	<b>3</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-0380-01</b>	<b>115-230V/1PH</b>	<b>3</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-0380-01M</b>	<b>230V/1PH</b>	<b>3</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-0380-02</b>	<b>200-208V/3PH</b>	<b>3</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-0380-02M</b>	<b>200-208V/3PH</b>	<b>3</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.

<b>BF-0380-03</b>	<b>230-240V/3PH</b>	<b>3</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-0380-03M</b>	<b>230-240V/3PH</b>	<b>3</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-0380-04</b>	<b>460-480V/3PH</b>	<b>3</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-0380-04M</b>	<b>460-480V/3PH</b>	<b>3</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-0380-05</b>	<b>575-600V/3PH</b>	<b>3</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-0380-05M</b>	<b>575-600V/3PH</b>	<b>3</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-0380-115M</b>	<b>115V/1PH</b>	<b>3</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-5080-01</b>	<b>230V/1PH</b>	<b>5</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.

<b>BF-5080-01M</b>	<b>230V/1PH</b>	<b>5</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-5080-02</b>	<b>200-208V/3PH</b>	<b>5</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-5080-02M</b>	<b>200-208V/3PH</b>	<b>5</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-5080-03</b>	<b>230-240V/3PH</b>	<b>5</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-5080-03M</b>	<b>230-240V/3PH</b>	<b>5</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-5080-04</b>	<b>460-480V/3PH</b>	<b>5</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-5080-04M</b>	<b>460-480V/3PH</b>	<b>5</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-5080-05</b>	<b>575-600V/3PH</b>	<b>5</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.

<b>BF-5080-05M</b>	<b>575-600V/3PH</b>	<b>5</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-50120-01</b>	<b>230V/1PH</b>	<b>5</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-50120-01M</b>	<b>230V/1PH</b>	<b>5</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-50120-02</b>	<b>200-208V/3PH</b>	<b>5</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-50120-02M</b>	<b>200-208V/3PH</b>	<b>5</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-50120-03</b>	<b>230-240V/3PH</b>	<b>5</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-50120-03M</b>	<b>230-240V/3PH</b>	<b>5</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-50120-04</b>	<b>460-480V/3PH</b>	<b>5</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.

<b>BF-50120-04M</b>	<b>460-480V/3PH</b>	<b>5</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-50120-05</b>	<b>575-600V/3PH</b>	<b>5</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-50120-05M</b>	<b>575-600V/3PH</b>	<b>5</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-7580-02</b>	<b>200-208V/3PH</b>	<b>7.5</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-7580-02M</b>	<b>200-208V/3PH</b>	<b>7.5</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-7580-03</b>	<b>230-240V/3PH</b>	<b>7.5</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-7580-03M</b>	<b>230-240V/3PH</b>	<b>7.5</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-7580-04</b>	<b>460-480V/3PH</b>	<b>7.5</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.

<b>BF-7580-04M</b>	<b>460-480V/3PH</b>	<b>7.5</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-7580-05</b>	<b>575-600V/3PH</b>	<b>7.5</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-7580-05M</b>	<b>575-600V/3PH</b>	<b>7.5</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-75120-02</b>	<b>200-208V/3PH</b>	<b>7.5</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-75120-02M</b>	<b>200-208V/3PH</b>	<b>7.5</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-75120-03</b>	<b>230-240V/3PH</b>	<b>7.5</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-75120-03M</b>	<b>230-240V/3PH</b>	<b>7.5</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-75120-04</b>	<b>460-480V/3PH</b>	<b>7.5</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.

<b>BF-75120-04M</b>	<b>460-480V/3PH</b>	<b>7.5</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-75120-05</b>	<b>575-600V/3PH</b>	<b>7.5</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-75120-05M</b>	<b>575-600V/3PH</b>	<b>7.5</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-100120-02</b>	<b>200-208V/3PH</b>	<b>10</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-100120-02M</b>	<b>200-208V/3PH</b>	<b>10</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-100120-03</b>	<b>230-240V/3PH</b>	<b>10</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-100120-03M</b>	<b>230-240V/3PH</b>	<b>10</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-100120-04</b>	<b>460-480V/3PH</b>	<b>10</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.

<b>BF-100120-04M</b>	<b>460-480V/3PH</b>	<b>10</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-100120-05</b>	<b>575-600V/3PH</b>	<b>10</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-100120-05M</b>	<b>575-600V/3PH</b>	<b>10</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-100240-02</b>	<b>200-208V/3PH</b>	<b>10</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-100240-02M</b>	<b>200-208V/3PH</b>	<b>10</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-100240-03</b>	<b>230-240V/3PH</b>	<b>10</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-100240-03M</b>	<b>230-240V/3PH</b>	<b>10</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-100240-04</b>	<b>460-480V/3PH</b>	<b>10</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.

<b>BF-100240-04M</b>	<b>460-480V/3PH</b>	<b>10</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-100240-05</b>	<b>575-600V/3PH</b>	<b>10</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-100240-05M</b>	<b>575-600V/3PH</b>	<b>10</b>	Oil-free air compressor, simplex tank mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Factory tested prior to shipment. 2-year limited manufacturer's warranty.

## OIL FREE SERIES - BASE MOUNTED SERIES

MODEL NO.	VOLTAGE	HP	DESCRIPTION
<b>BF-0200-01</b>	<b>115-230V/1PH</b>	<b>2</b>	Oil-free air compressor, base mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-0200-01M</b>	<b>230V/1PH</b>	<b>2</b>	Oil-free air compressor, base mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-0200-02</b>	<b>200-208V/3PH</b>	<b>2</b>	Oil-free air compressor, base mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-0200-02M</b>	<b>200-208V/3PH</b>	<b>2</b>	Oil-free air compressor, base mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Factory tested prior to shipment. 2-year limited manufacturer's warranty.

<b>BF-0200-03</b>	<b>230-240V/3PH</b>	<b>2</b>	Oil-free air compressor, base mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-0200-03M</b>	<b>230-240V/3PH</b>	<b>2</b>	Oil-free air compressor, base mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-0200-04</b>	<b>460-480V/3PH</b>	<b>2</b>	Oil-free air compressor, base mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-0200-04M</b>	<b>460-480V/3PH</b>	<b>2</b>	Oil-free air compressor, base mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-0200-05</b>	<b>575-600V/3PH</b>	<b>2</b>	Oil-free air compressor, base mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-0200-05M</b>	<b>575-600V/3PH</b>	<b>2</b>	Oil-free air compressor, base mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-0200-115M</b>	<b>115V/1PH</b>	<b>2</b>	Oil-free air compressor, base mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-0300-01</b>	<b>115-230V/1PH</b>	<b>3</b>	Oil-free air compressor, base mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Factory tested prior to shipment. 2-year limited manufacturer's warranty.

<b>BF-0300-01M</b>	<b>230V/1PH</b>	<b>3</b>	Oil-free air compressor, base mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-0300-02</b>	<b>200-208V/3PH</b>	<b>3</b>	Oil-free air compressor, base mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-0300-02M</b>	<b>200-208V/3PH</b>	<b>3</b>	Oil-free air compressor, base mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-0300-03</b>	<b>230-240V/3PH</b>	<b>3</b>	Oil-free air compressor, base mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-0300-03M</b>	<b>230-240V/3PH</b>	<b>3</b>	Oil-free air compressor, base mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-0300-04</b>	<b>460-480V/3PH</b>	<b>3</b>	Oil-free air compressor, base mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-0300-04M</b>	<b>460-480V/3PH</b>	<b>3</b>	Oil-free air compressor, base mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-0300-05</b>	<b>575-600V/3PH</b>	<b>3</b>	Oil-free air compressor, base mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Factory tested prior to shipment. 2-year limited manufacturer's warranty.

<b>BF-0300-05M</b>	<b>575-600V/3PH</b>	<b>3</b>	Oil-free air compressor, base mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-0300-115M</b>	<b>115V/1PH</b>	<b>3</b>	Oil-free air compressor, base mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-5000-01</b>	<b>230V/1PH</b>	<b>5</b>	Oil-free air compressor, base mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-5000-01M</b>	<b>230V/1PH</b>	<b>5</b>	Oil-free air compressor, base mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-5000-02</b>	<b>200-208V/3PH</b>	<b>5</b>	Oil-free air compressor, base mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-5000-02M</b>	<b>200-208V/3PH</b>	<b>5</b>	Oil-free air compressor, base mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-5000-03</b>	<b>230-240V/3PH</b>	<b>5</b>	Oil-free air compressor, base mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-5000-03M</b>	<b>230-240V/3PH</b>	<b>5</b>	Oil-free air compressor, base mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Factory tested prior to shipment. 2-year limited manufacturer's warranty.

<b>BF-5000-04</b>	<b>460-480V/3PH</b>	<b>5</b>	Oil-free air compressor, base mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-5000-04M</b>	<b>460-480V/3PH</b>	<b>5</b>	Oil-free air compressor, base mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-5000-05</b>	<b>575-600V/3PH</b>	<b>5</b>	Oil-free air compressor, base mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-5000-05M</b>	<b>575-600V/3PH</b>	<b>5</b>	Oil-free air compressor, base mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-7500-02</b>	<b>200-208V/3PH</b>	<b>7.5</b>	Oil-free air compressor, base mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-7500-02M</b>	<b>200-208V/3PH</b>	<b>7.5</b>	Oil-free air compressor, base mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-7500-03</b>	<b>230-240V/3PH</b>	<b>7.5</b>	Oil-free air compressor, base mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-7500-03M</b>	<b>230-240V/3PH</b>	<b>7.5</b>	Oil-free air compressor, base mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Factory tested prior to shipment. 2-year limited manufacturer's warranty.

<b>BF-7500-04</b>	<b>460-480V/3PH</b>	<b>7.5</b>	Oil-free air compressor, base mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-7500-04M</b>	<b>460-480V/3PH</b>	<b>7.5</b>	Oil-free air compressor, base mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-7500-05</b>	<b>575-600V/3PH</b>	<b>7.5</b>	Oil-free air compressor, base mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-7500-05M</b>	<b>575-600V/3PH</b>	<b>7.5</b>	Oil-free air compressor, base mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-100000-02</b>	<b>200-208V/3PH</b>	<b>10</b>	Oil-free air compressor, base mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-100000-02M</b>	<b>200-208V/3PH</b>	<b>10</b>	Oil-free air compressor, base mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-100000-03</b>	<b>230-240V/3PH</b>	<b>10</b>	Oil-free air compressor, base mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-100000-03M</b>	<b>230-240V/3PH</b>	<b>10</b>	Oil-free air compressor, base mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Factory tested prior to shipment. 2-year limited manufacturer's warranty.

<b>BF-100000-04</b>	<b>460-480V/3PH</b>	<b>10</b>	Oil-free air compressor, base mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-100000-04M</b>	<b>460-480V/3PH</b>	<b>10</b>	Oil-free air compressor, base mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-100000-05</b>	<b>575-600V/3PH</b>	<b>10</b>	Oil-free air compressor, base mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-100000-05M</b>	<b>575-600V/3PH</b>	<b>10</b>	Oil-free air compressor, base mounted. Heavy duty single and two stage high efficient oil-free cast iron pump with stainless steel valves. Durable cast iron pump for performance and durability. Factory tested prior to shipment. 2-year limited manufacturer's warranty.

## OIL FREE SERIES - DUPLEX SERIES

<b>MODEL NO.</b>	<b>VOLTAGE</b>	<b>HP</b>	<b>DESCRIPTION</b>
<b>BF-DX-0230-01</b>	<b>115-230V/1PH</b>	<b>2</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-0230-01ALT</b>	<b>230V/1PH</b>	<b>2</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-0230-02</b>	<b>200-208V/3PH</b>	<b>2</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.

<b>BF-DX-0230-02ALT</b>	<b>200-208V/3PH</b>	<b>2</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-0230-03</b>	<b>230-240V/3PH</b>	<b>2</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-0230-03ALT</b>	<b>230-240V/3PH</b>	<b>2</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-0230-04</b>	<b>460-480V/3PH</b>	<b>2</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-0230-04ALT</b>	<b>460-480V/3PH</b>	<b>2</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-0230-05</b>	<b>575-600V/3PH</b>	<b>2</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-0230-05ALT</b>	<b>575-600V/3PH</b>	<b>2</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-0230-115ALT</b>	<b>115V/1PH</b>	<b>2</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.

<b>BF-DX-0260-01</b>	<b>115-230V/1PH</b>	<b>2</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-0260-01ALT</b>	<b>230V/1PH</b>	<b>2</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-0260-02</b>	<b>200-208V/3PH</b>	<b>2</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-0260-02ALT</b>	<b>200-208V/3PH</b>	<b>2</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-0260-03</b>	<b>230-240V/3PH</b>	<b>2</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-0260-03ALT</b>	<b>230-240V/3PH</b>	<b>2</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-0260-04</b>	<b>460-480V/3PH</b>	<b>2</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-0260-04ALT</b>	<b>460-480V/3PH</b>	<b>2</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.

<b>BF-DX-0260-05</b>	<b>575-600V/3PH</b>	<b>2</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-0260-05ALT</b>	<b>575-600V/3PH</b>	<b>2</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-0260-115ALT</b>	<b>115-230V/1PH</b>	<b>2</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-0280-01</b>	<b>115-230V/1PH</b>	<b>2</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-0280-01ALT</b>	<b>230V/1PH</b>	<b>2</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-0280-02</b>	<b>200-208V/3PH</b>	<b>2</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-0280-02ALT</b>	<b>200-208V/3PH</b>	<b>2</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-0280-03</b>	<b>230-240V/3PH</b>	<b>2</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.

<b>BF-DX-0280-03ALT</b>	<b>230-240V/3PH</b>	<b>2</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-0280-04</b>	<b>460-480V/3PH</b>	<b>2</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-0280-04ALT</b>	<b>460-480V/3PH</b>	<b>2</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-0280-05</b>	<b>575-600V/3PH</b>	<b>2</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-0280-05ALT</b>	<b>575-600V/3PH</b>	<b>2</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-0280-115ALT</b>	<b>115-230V/1PH</b>	<b>2</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-0380-01</b>	<b>115-230V/1PH</b>	<b>3</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-0380-01ALT</b>	<b>230V/1PH</b>	<b>3</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.

<b>BF-DX-0380-02</b>	<b>200-208V/3PH</b>	<b>3</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-0380-02ALT</b>	<b>200-208V/3PH</b>	<b>3</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-0380-03</b>	<b>230-240V/3PH</b>	<b>3</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-0380-03ALT</b>	<b>230-240V/3PH</b>	<b>3</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-0380-04</b>	<b>460-480V/3PH</b>	<b>3</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-0380-04ALT</b>	<b>460-480V/3PH</b>	<b>3</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-0380-05</b>	<b>575-600V/3PH</b>	<b>3</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-0380-05ALT</b>	<b>575-600V/3PH</b>	<b>3</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.

<b>BF-DX-0380-115ALT</b>	<b>115V/1PH</b>	<b>3</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-03120-01</b>	<b>115-230V/1PH</b>	<b>3</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-03120-01ALT</b>	<b>230V/1PH</b>	<b>3</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-03120-02</b>	<b>200-208V/3PH</b>	<b>3</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-03120-02ALT</b>	<b>200-208V/3PH</b>	<b>3</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-03120-03</b>	<b>230-240V/3PH</b>	<b>3</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-03120-03ALT</b>	<b>230-240V/3PH</b>	<b>3</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-03120-04</b>	<b>460-480V/3PH</b>	<b>3</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.

<b>BF-DX-03120-04ALT</b>	<b>460-480V/3PH</b>	<b>3</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-03120-05</b>	<b>575-600V/3PH</b>	<b>3</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-03120-05ALT</b>	<b>575-600V/3PH</b>	<b>3</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-03120-115ALT</b>	<b>115V/1PH</b>	<b>3</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-50120-01</b>	<b>230V/1PH</b>	<b>5</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-50120-01ALT</b>	<b>230V/1PH</b>	<b>5</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-50120-02</b>	<b>200-208V/3PH</b>	<b>5</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-50120-02ALT</b>	<b>200-208V/3PH</b>	<b>5</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.

<b>BF-DX-50120-03</b>	<b>230-240V/3PH</b>	<b>5</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-50120-03ALT</b>	<b>230-240V/3PH</b>	<b>5</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-50120-04</b>	<b>460-480V/3PH</b>	<b>5</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-50120-04ALT</b>	<b>460-480V/3PH</b>	<b>5</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-50120-05</b>	<b>575-600V/3PH</b>	<b>5</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-50120-05ALT</b>	<b>575-600V/3PH</b>	<b>5</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-75120-02</b>	<b>200-208V/3PH</b>	<b>7.5</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-75120-02ALT</b>	<b>200-208V/3PH</b>	<b>7.5</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.

<b>BF-DX-75120-03</b>	<b>230-240V/3PH</b>	<b>7.5</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-75120-03ALT</b>	<b>230-240V/3PH</b>	<b>7.5</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-75120-04</b>	<b>460-480V/3PH</b>	<b>7.5</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-75120-04ALT</b>	<b>460-480V/3PH</b>	<b>7.5</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-75120-05</b>	<b>575-600V/3PH</b>	<b>7.5</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-75120-05ALT</b>	<b>575-600V/3PH</b>	<b>7.5</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-75240-02</b>	<b>200-208V/3PH</b>	<b>7.5</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-75240-02ALT</b>	<b>200-208V/3PH</b>	<b>7.5</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.

<b>BF-DX-75240-03</b>	<b>230-240V/3PH</b>	<b>7.5</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-75240-03ALT</b>	<b>230-240V/3PH</b>	<b>7.5</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-75240-04</b>	<b>460-480V/3PH</b>	<b>7.5</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-75240-04ALT</b>	<b>460-480V/3PH</b>	<b>7.5</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-75240-05</b>	<b>575-600V/3PH</b>	<b>7.5</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-75240-05ALT</b>	<b>575-600V/3PH</b>	<b>7.5</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-100120-02</b>	<b>200-208V/3PH</b>	<b>10</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-100120-02ALT</b>	<b>200-208V/3PH</b>	<b>10</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.

<b>BF-DX-100120-03</b>	<b>230-240V/3PH</b>	<b>10</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-100120-03ALT</b>	<b>230-240V/3PH</b>	<b>10</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-100120-04</b>	<b>460-480V/3PH</b>	<b>10</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-100120-04ALT</b>	<b>460-480V/3PH</b>	<b>10</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-100120-05</b>	<b>575-600V/3PH</b>	<b>10</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-100120-05ALT</b>	<b>575-600V/3PH</b>	<b>10</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-100240-02</b>	<b>200-208V/3PH</b>	<b>10</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-100240-02ALT</b>	<b>200-208V/3PH</b>	<b>10</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.

<b>BF-DX-100240-03</b>	<b>230-240V/3PH</b>	<b>10</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-100240-03ALT</b>	<b>230-240V/3PH</b>	<b>10</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-100240-04</b>	<b>460-480V/3PH</b>	<b>10</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-100240-04ALT</b>	<b>460-480V/3PH</b>	<b>10</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-100240-05</b>	<b>575-600V/3PH</b>	<b>10</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.
<b>BF-DX-100240-05ALT</b>	<b>575-600V/3PH</b>	<b>10</b>	Oil-free air compressor, duplex configuration. Heavy duty single and two stage high efficient oil-free cast iron pumps with stainless steel valves. Durable cast iron pumps for performance and durability. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Set up for lead lag operation. Factory tested prior to shipment. 2-year limited manufacturer's warranty.

## FIRE SPRINKLER SERIES - TANK MOUNTED SERIES

MODEL NO.	VOLTAGE	HP	DESCRIPTION
<b>FS-0520-01</b>	<b>115-230V/1PH</b>	<b>2</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.

<b>FS-0520-01M</b>	<b>230V/1PH</b>	<b>2</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-0520-02</b>	<b>200-208V/3PH</b>	<b>2</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-0520-02M</b>	<b>200-208V/3PH</b>	<b>2</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-0520-03</b>	<b>230-240V/3PH</b>	<b>2</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-0520-03M</b>	<b>230-240V/3PH</b>	<b>2</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-0520-04</b>	<b>460-480V/3PH</b>	<b>2</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-0520-04M</b>	<b>460-480V/3PH</b>	<b>2</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-0520-05</b>	<b>575-600V/3PH</b>	<b>2</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.

<b>FS-0520-05M</b>	<b>575-600V/3PH</b>	<b>2</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-0520-115M</b>	<b>115V/1PH</b>	<b>2</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-07520-01</b>	<b>115-230V/1PH</b>	<b>4</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-07520-01M</b>	<b>230V/1PH</b>	<b>4</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-07520-02</b>	<b>200-208V/3PH</b>	<b>4</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-07520-02M</b>	<b>200-208V/3PH</b>	<b>4</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-07520-03</b>	<b>230-240V/3PH</b>	<b>4</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-07520-03M</b>	<b>230-240V/3PH</b>	<b>4</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.

<b>FS-07520-04</b>	<b>460-480V/3PH</b>	<b>4</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-07520-04M</b>	<b>460-480V/3PH</b>	<b>4</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-07520-05</b>	<b>575-600V/3PH</b>	<b>4</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-07520-05M</b>	<b>575-600V/3PH</b>	<b>4</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-07520-115M</b>	<b>115V/1PH</b>	<b>4</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-0120-01</b>	<b>115-230V/1PH</b>	<b>1</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-0120-01M</b>	<b>230V/1PH</b>	<b>1</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-0120-02</b>	<b>200-208V/3PH</b>	<b>1</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.

<b>FS-0120-02M</b>	<b>200-208V/3PH</b>	<b>1</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-0120-03</b>	<b>230-240V/3PH</b>	<b>1</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-0120-03M</b>	<b>230-240V/3PH</b>	<b>1</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-0120-04</b>	<b>460-480V/3PH</b>	<b>1</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-0120-04M</b>	<b>460-480V/3PH</b>	<b>1</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-0120-05</b>	<b>575-600V/3PH</b>	<b>1</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-0120-05M</b>	<b>575-600V/3PH</b>	<b>1</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-0120-115M</b>	<b>115V/1PH</b>	<b>1</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.

<b>FS-01520-01</b>	<b>115-230V/1PH</b>	<b>2</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-01520-01M</b>	<b>230V/1PH</b>	<b>2</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-01520-02</b>	<b>200-208V/3PH</b>	<b>2</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-01520-02M</b>	<b>200-208V/3PH</b>	<b>2</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-01520-03</b>	<b>230-240V/3PH</b>	<b>2</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-01520-03M</b>	<b>230-240V/3PH</b>	<b>2</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-01520-04</b>	<b>460-480V/3PH</b>	<b>2</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-01520-04M</b>	<b>460-480V/3PH</b>	<b>2</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.

<b>FS-01520-05</b>	<b>575-600V/3PH</b>	<b>2</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-01520-05M</b>	<b>575-600V/3PH</b>	<b>2</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-01520-115M</b>	<b>115V/1PH</b>	<b>2</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-0220-01</b>	<b>115-230V/1PH</b>	<b>2</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-0220-01M</b>	<b>230V/1PH</b>	<b>2</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-0220-02</b>	<b>200-208V/3PH</b>	<b>2</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-0220-02M</b>	<b>200-208V/3PH</b>	<b>2</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-0220-03</b>	<b>230-240V/3PH</b>	<b>2</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.

<b>FS-0220-03M</b>	<b>230-240V/3PH</b>	<b>2</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-0220-04</b>	<b>460-480V/3PH</b>	<b>2</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-0220-04M</b>	<b>460-480V/3PH</b>	<b>2</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-0220-05</b>	<b>575-600V/3PH</b>	<b>2</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-0220-05M</b>	<b>575-600V/3PH</b>	<b>2</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-0220-115M</b>	<b>115V/1PH</b>	<b>2</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-0320-01</b>	<b>230V/1PH</b>	<b>3</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-0320-01M</b>	<b>230V/1PH</b>	<b>3</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.

<b>FS-0320-02</b>	<b>200-208V/3PH</b>	<b>3</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-0320-02M</b>	<b>200-208V/3PH</b>	<b>3</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-0320-03</b>	<b>230-240V/3PH</b>	<b>3</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-0320-03M</b>	<b>230-240V/3PH</b>	<b>3</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-0320-04</b>	<b>460-480V/3PH</b>	<b>3</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-0320-04M</b>	<b>460-480V/3PH</b>	<b>3</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-0320-05</b>	<b>575-600V/3PH</b>	<b>3</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-0320-05M</b>	<b>575-600V/3PH</b>	<b>3</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.

<b>FS-5020-01</b>	<b>230V/1PH</b>	<b>5</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-5020-01M</b>	<b>230V/1PH</b>	<b>5</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-5020-02</b>	<b>208V/3PH</b>	<b>5</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-5020-02M</b>	<b>208V/3PH</b>	<b>5</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-5020-03</b>	<b>230V/3PH</b>	<b>5</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-5020-03M</b>	<b>230V/3PH</b>	<b>5</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-5020-04</b>	<b>460V/3PH</b>	<b>5</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-5020-04M</b>	<b>460V/3PH</b>	<b>5</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.

<b>FS-5020-05</b>	<b>575-600V/3PH</b>	<b>5</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-5020-05M</b>	<b>575-600V/3PH</b>	<b>5</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-5060-01</b>	<b>230V/1PH</b>	<b>5</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-5060-01M</b>	<b>230V/1PH</b>	<b>5</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-5060-02</b>	<b>200-208V/3PH</b>	<b>5</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-5060-02M</b>	<b>200-208V/3PH</b>	<b>5</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-5060-03</b>	<b>230-240V/3PH</b>	<b>5</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-5060-03M</b>	<b>230-240V/3PH</b>	<b>5</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.

<b>FS-5060-04</b>	<b>460-480V/3PH</b>	<b>5</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-5060-04M</b>	<b>460-480V/3PH</b>	<b>5</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-5060-05</b>	<b>575-600V/3PH</b>	<b>5</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.
<b>FS-5060-05M</b>	<b>575-600V/3PH</b>	<b>5</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. All units factory set at 30-50 PSI. Mounted on air receiver rated at 200 PSI, CRN approved for Canada. Extended drain valve. Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: low oil shutdown with magnetic starter c/w 24V step-down transformer, auto drain (electronic or pneumatic), belt guard aftercooler.

## FIRE SPRINKLER SERIES - BASE MOUNTED SERIES

<b>MODEL NO.</b>	<b>VOLTAGE</b>	<b>HP</b>	<b>DESCRIPTION</b>
<b>FS-0500-01</b>	<b>115-230V/1PH</b>	<b>2</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Pressure switch, safety valve, gauge, check valve, aftercooler tube and manifold NOT included (available with Auto Control Group FSC-ACG). Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: FSC-ACG Auto Control Group (pressure switch 30-50 PSI, snubber, safety valve, liquid filled gauge and manifold, check valve, aftercooler tube, flex hose), low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler.
<b>FS-0500-01M</b>	<b>230V/1PH</b>	<b>2</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Pressure switch, safety valve, gauge, check valve, aftercooler tube and manifold NOT included (available with Auto Control Group FSC-ACG). Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: FSC-ACG Auto Control Group (pressure switch 30-50 PSI, snubber, safety valve, liquid filled gauge and manifold, check valve, aftercooler tube, flex hose), low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler.
<b>FS-0500-02</b>	<b>200-208V/3PH</b>	<b>2</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Pressure switch, safety valve, gauge, check valve, aftercooler tube and manifold NOT included (available with Auto Control Group FSC-ACG). Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: FSC-ACG Auto Control Group (pressure switch 30-50 PSI, snubber, safety valve, liquid filled gauge and manifold, check valve, aftercooler tube, flex hose), low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler.





<b>FS-07500-05</b>	<b>575-600V/3PH</b>	<b>4</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Pressure switch, safety valve, gauge, check valve, aftercooler tube and manifold NOT included (available with Auto Control Group FSC-ACG). Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: FSC-ACG Auto Control Group (pressure switch 30-50 PSI, snubber, safety valve, liquid filled gauge and manifold, check valve, aftercooler tube, flex hose), low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler.
<b>FS-07500-05M</b>	<b>575-600V/3PH</b>	<b>4</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Pressure switch, safety valve, gauge, check valve, aftercooler tube and manifold NOT included (available with Auto Control Group FSC-ACG). Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: FSC-ACG Auto Control Group (pressure switch 30-50 PSI, snubber, safety valve, liquid filled gauge and manifold, check valve, aftercooler tube, flex hose), low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler.
<b>FS-07500-115M</b>	<b>115V/1PH</b>	<b>4</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Pressure switch, safety valve, gauge, check valve, aftercooler tube and manifold NOT included (available with Auto Control Group FSC-ACG). Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: FSC-ACG Auto Control Group (pressure switch 30-50 PSI, snubber, safety valve, liquid filled gauge and manifold, check valve, aftercooler tube, flex hose), low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler.
<b>FS-0100-01</b>	<b>115-230V/1PH</b>	<b>1</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Pressure switch, safety valve, gauge, check valve, aftercooler tube and manifold NOT included (available with Auto Control Group FSC-ACG). Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: FSC-ACG Auto Control Group (pressure switch 30-50 PSI, snubber, safety valve, liquid filled gauge and manifold, check valve, aftercooler tube, flex hose), low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler.
<b>FS-0100-01M</b>	<b>230V/1PH</b>	<b>1</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Pressure switch, safety valve, gauge, check valve, aftercooler tube and manifold NOT included (available with Auto Control Group FSC-ACG). Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: FSC-ACG Auto Control Group (pressure switch 30-50 PSI, snubber, safety valve, liquid filled gauge and manifold, check valve, aftercooler tube, flex hose), low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler.
<b>FS-0100-02</b>	<b>200-208V/3PH</b>	<b>1</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Pressure switch, safety valve, gauge, check valve, aftercooler tube and manifold NOT included (available with Auto Control Group FSC-ACG). Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: FSC-ACG Auto Control Group (pressure switch 30-50 PSI, snubber, safety valve, liquid filled gauge and manifold, check valve, aftercooler tube, flex hose), low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler.
<b>FS-0100-02M</b>	<b>200-208V/3PH</b>	<b>1</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Pressure switch, safety valve, gauge, check valve, aftercooler tube and manifold NOT included (available with Auto Control Group FSC-ACG). Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: FSC-ACG Auto Control Group (pressure switch 30-50 PSI, snubber, safety valve, liquid filled gauge and manifold, check valve, aftercooler tube, flex hose), low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler.
<b>FS-0100-03</b>	<b>230-240V/3PH</b>	<b>1</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Pressure switch, safety valve, gauge, check valve, aftercooler tube and manifold NOT included (available with Auto Control Group FSC-ACG). Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: FSC-ACG Auto Control Group (pressure switch 30-50 PSI, snubber, safety valve, liquid filled gauge and manifold, check valve, aftercooler tube, flex hose), low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler.







<b>FS-0200-04M</b>	<b>460-480V/3PH</b>	<b>2</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Pressure switch, safety valve, gauge, check valve, aftercooler tube and manifold NOT included (available with Auto Control Group FSC-ACG). Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: FSC-ACG Auto Control Group (pressure switch 30-50 PSI, snubber, safety valve, liquid filled gauge and manifold, check valve, aftercooler tube, flex hose), low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler.
<b>FS-0200-05</b>	<b>575-600V/3PH</b>	<b>2</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Pressure switch, safety valve, gauge, check valve, aftercooler tube and manifold NOT included (available with Auto Control Group FSC-ACG). Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: FSC-ACG Auto Control Group (pressure switch 30-50 PSI, snubber, safety valve, liquid filled gauge and manifold, check valve, aftercooler tube, flex hose), low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler.
<b>FS-0200-05M</b>	<b>575-600V/3PH</b>	<b>2</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Pressure switch, safety valve, gauge, check valve, aftercooler tube and manifold NOT included (available with Auto Control Group FSC-ACG). Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: FSC-ACG Auto Control Group (pressure switch 30-50 PSI, snubber, safety valve, liquid filled gauge and manifold, check valve, aftercooler tube, flex hose), low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler.
<b>FS-0200-115M</b>	<b>115V/1PH</b>	<b>2</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Pressure switch, safety valve, gauge, check valve, aftercooler tube and manifold NOT included (available with Auto Control Group FSC-ACG). Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: FSC-ACG Auto Control Group (pressure switch 30-50 PSI, snubber, safety valve, liquid filled gauge and manifold, check valve, aftercooler tube, flex hose), low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler.
<b>FS-0300-01</b>	<b>115-230V/1PH</b>	<b>3</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Pressure switch, safety valve, gauge, check valve, aftercooler tube and manifold NOT included (available with Auto Control Group FSC-ACG). Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: FSC-ACG Auto Control Group (pressure switch 30-50 PSI, snubber, safety valve, liquid filled gauge and manifold, check valve, aftercooler tube, flex hose), low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler.
<b>FS-0300-01M</b>	<b>230V/1PH</b>	<b>3</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Pressure switch, safety valve, gauge, check valve, aftercooler tube and manifold NOT included (available with Auto Control Group FSC-ACG). Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: FSC-ACG Auto Control Group (pressure switch 30-50 PSI, snubber, safety valve, liquid filled gauge and manifold, check valve, aftercooler tube, flex hose), low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler.
<b>FS-0300-02</b>	<b>200-208V/3PH</b>	<b>3</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Pressure switch, safety valve, gauge, check valve, aftercooler tube and manifold NOT included (available with Auto Control Group FSC-ACG). Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: FSC-ACG Auto Control Group (pressure switch 30-50 PSI, snubber, safety valve, liquid filled gauge and manifold, check valve, aftercooler tube, flex hose), low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler.
<b>FS-0300-02M</b>	<b>200-208V/3PH</b>	<b>3</b>	Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Pressure switch, safety valve, gauge, check valve, aftercooler tube and manifold NOT included (available with Auto Control Group FSC-ACG). Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: FSC-ACG Auto Control Group (pressure switch 30-50 PSI, snubber, safety valve, liquid filled gauge and manifold, check valve, aftercooler tube, flex hose), low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler.





<p><b>FS-ACG</b></p>		<p>Heavy duty single stage high efficient cast iron air compressor for fire sprinkler systems. Splash type lubrication. Stainless steel valves. Flywheel pump cooling. Oil sight gauge. Pressure switch, safety valve, gauge, check valve, aftercooler tube and manifold NOT included (available with Auto Control Group FSC-ACG). Magnetic starter available (supplied loose). Supplied with compressor oil for start up. Factory tested prior to shipment. 2-year limited manufacturer's warranty. Factory mounted options available: FSC-ACG Auto Control Group (pressure switch 90-50 PSI, snubber, safety valve, liquid filled gauge and manifold, check valve, aftercooler tube, flex hose), low oil shutdown with magnetic starter c/w 24V step-down transformer, belt guard aftercooler.</p>
----------------------	--	--